

● Specification

Model	HS-400W	HS-800W
Auxiliary engine output	40.3 kW / 2,100 min ⁻¹	98 kW / 2,000 min ⁻¹
Hopper volume	3.4 m ³	6.4 m ³
Typical payload	1.6 - 1.9 ton*	3 - 4 ton*
Max sweeping width	2,400 mm	3,500 mm
Sweeping speed	3 - 20 km / h	3 - 30 km / h
Air flow	190 m ³ / min	380 m ³ / min
Water tank capacity	900 L	1,600 L
Fuel tank capacity	100 L	200 L
Typical chassis G.V.W.	7.5t*	15t*

* depending on chassis type

KATO

Street Sweeper

HS-400W
HS-800W

Street-Master

HS-400W
Street-Master

(Unit: mm)

① Sweeping width

① Suction port	1,200mm
② Single gutter brush & single port	1,200mm
③ Single gutter brush & double port	1,800mm
④ Full-size sweep (optional)	2,400mm

Dimensions (typical chassis selection)

HS-800W
Street-Master

(Unit: mm)

① Sweeping width

① Suction port	1,400mm
② Single gutter brush & single port	1,750mm
③ Single gutter brush & double port	2,450mm
④ Full-size sweep (optional)	3,500mm

Dimensions (typical chassis selection)



Option Specification



Option Specification

<http://www.kato-works.co.jp>

NOTE : Illustrations may include optional equipment. KATO products and specifications are subject to improvements and changes without notice.

● Contact for enquiry:



Obtained authentication of International Specification ISO9001 for quality assurance.

KATO
QUALITY & EXPERIENCE
SINCE 1895

KATO WORKS CO.,LTD.

9-37, Higashi-ohi 1-chome, Shinagawa-ku, Tokyo 140-0011, Japan.
Tel. : Head Office Tokyo(03)3458-1111
Overseas Marketing Department Tokyo(03)3458-1115
Fax. : Tokyo(03)3458-1163

Progress to the Next Stage

KATO WORKS CO.,LTD.

High Performance Street Sweeper, Friendly to People, City and Environment

- Powerful Vacuum Performance
- Compact Body
- Selectable (Left / Right / Full-size) Brush Operation
- Lower Noise Emission and Excellent Drivability
- Simple and Tough Mechanism for Easy Maintenance and Lower Running Cost



HS-400W



HS-800W