



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SA性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	76.2	20.0	77.8	19.7	79.8	16.7	81.3	14.8	82.2	12.9
20.0	74.6	20.0	76.1	18.6	78.1	16.1	79.5	14.4	80.2	12.7
22.0	73.0	20.0	74.3	17.7	76.2	15.5	77.6	14.1	78.2	12.5
24.0	71.1	18.8	72.5	16.8	74.3	15.0	75.6	13.9	76.2	12.3
26.0	69.2	17.1	70.7	16.1	72.4	14.6	73.6	13.6	74.1	12.1
28.0	67.2	15.7	68.7	15.0	70.5	14.2	71.6	13.2	72.0	12.0
30.0	65.2	14.4	66.6	13.8	68.4	13.2	69.4	12.8	69.8	11.9
32.0	63.0	13.3	64.5	12.8	66.2	12.2	67.3	11.9	67.4	11.8
34.0	60.8	11.4	62.4	11.9	64.0	11.4	64.9	11.2		
36.0	58.4	9.6	60.0	10.3	61.8	10.6	62.4	10.5		
38.0	56.0	8.1	57.6	8.7	59.3	9.4	59.9	9.8		
40.0	53.6	6.7	55.0	7.2	56.6	7.8	57.2	8.2		
42.0	51.0	5.4	52.5	5.9	53.9	6.5	54.4	6.7		
44.0	48.3	4.3	49.8	4.7	51.1	5.2	51.4	5.4		
46.0	45.5	3.2	46.9	3.6	48.1	4.0				
48.0					44.9	3.0				
危険角度 (°)	43		44		44		49.5		65.5	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SA性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.6	11.0	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	72.1	11.0	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.6	11.0	74.4	10.6	77.4	9.2	79.9	8.2	81.5	7.1
28.0	69.1	11.0	72.7	10.1	75.7	8.9	78.1	8.0	79.5	7.0
30.0	67.6	11.0	71.0	9.6	74.0	8.6	76.2	7.8	77.6	6.9
32.0	65.9	10.5	69.3	9.2	72.2	8.3	74.4	7.6	75.5	6.8
34.0	64.1	9.9	67.5	8.8	70.4	8.1	72.5	7.5	73.4	6.7
36.0	62.3	9.3	65.7	8.4	68.6	7.8	70.5	7.3	71.3	6.6
38.0	60.5	8.7	63.9	8.1	66.7	7.6	68.5	7.1	69.0	6.6
40.0	58.5	8.2	62.0	7.7	64.7	7.4	66.4	7.0	66.7	6.6
42.0	56.5	7.2	60.1	7.5	62.6	7.2	64.2	6.9		
44.0	54.4	6.1	58.1	7.2	60.4	7.0	61.9	6.8		
46.0	52.3	5.1	55.8	6.2	58.1	6.8	59.5	6.7		
48.0	49.9	4.1	53.4	5.1	55.8	5.9	57.0	6.4		
50.0	47.4	3.2	50.9	4.2	53.3	4.9	54.1	5.2		
52.0	44.9	2.4	48.3	3.3	50.5	3.9	51.0	4.2		
54.0			45.6	2.5	47.5	3.0				
56.0					44.4	2.1				
危険角度 (°)	43		44		44		50		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SA性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.5	7.5	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	70.2	7.5	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0	68.8	7.5	73.4	6.7	77.3	5.7	80.4	4.9	82.7	4.4
34.0	67.3	7.4	71.9	6.4	75.7	5.6	78.7	4.8	80.8	4.3
36.0	65.8	6.9	70.3	6.1	74.1	5.4	77.0	4.7	78.9	4.2
38.0	64.2	6.5	68.7	5.8	72.4	5.2	75.2	4.6	77.0	4.2
40.0	62.6	6.1	67.1	5.6	70.7	5.1	73.4	4.5	75.0	4.1
42.0	60.9	5.7	65.4	5.3	68.9	4.9	71.6	4.4	72.9	4.1
44.0	59.2	5.4	63.7	5.0	67.1	4.7	69.7	4.4	70.8	4.0
46.0	57.5	5.1	62.0	4.8	65.3	4.6	67.7	4.3	68.5	4.0
48.0	55.6	4.8	60.2	4.6	63.4	4.4	65.6	4.2	66.2	4.0
50.0	53.6	4.5	58.3	4.4	61.4	4.3	63.5	4.2		
52.0	51.6	3.9	56.2	4.2	59.4	4.2	61.2	4.1		
54.0	49.5	3.1	54.0	4.1	57.3	4.1	58.9	4.1		
56.0	47.3	2.4	51.8	3.5	54.9	4.0	56.2	4.0		
58.0	45.0	1.8	49.4	2.8	52.3	3.6	53.4	4.0		
60.0			47.0	2.1	49.7	2.8				
62.0			44.2	1.5	46.8	2.1				
危険角度 (°)	43		44		44		51		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SA性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.4	6.5	76.4	6.1	80.7	4.8	84.4	4.0		
32.0	70.1	6.5	75.0	5.9	79.2	4.7	82.8	3.9		
34.0	68.8	6.5	73.6	5.7	77.7	4.5	81.2	3.8	83.7	3.4
36.0	67.3	6.3	72.1	5.5	76.1	4.4	79.5	3.7	81.9	3.3
38.0	65.8	5.9	70.7	5.2	74.6	4.2	77.8	3.6	80.0	3.3
40.0	64.3	5.6	69.1	5.0	73.0	4.1	76.1	3.6	78.1	3.3
42.0	62.7	5.2	67.5	4.7	71.4	4.0	74.3	3.5	76.2	3.2
44.0	61.1	4.9	65.9	4.5	69.7	3.9	72.5	3.4	74.1	3.2
46.0	59.5	4.6	64.3	4.3	68.0	3.8	70.7	3.4	72.0	3.2
48.0	57.8	4.3	62.6	4.1	66.2	3.7	68.8	3.3	69.8	3.2
50.0	56.0	4.0	60.8	3.9	64.4	3.6	66.8	3.3	67.5	3.2
52.0	54.2	3.8	59.0	3.7	62.5	3.6	64.7	3.3		
54.0	52.2	3.6	57.1	3.6	60.5	3.5	62.5	3.2		
56.0	50.2	2.9	55.1	3.5	58.5	3.4	60.2	3.2		
58.0	48.2	2.3	52.9	3.3	56.4	3.4	57.8	3.2		
60.0	45.9	1.7	50.7	2.7	53.9	3.3	55.2	3.2		
62.0			48.4	2.1	51.4	2.9	52.4	3.2		
64.0			45.9	1.5	48.7	2.2				
66.0					45.8	1.5				
危険角度 (°)	43.5		44		44		51		65.5	
標準フック	12t		12t		12t		12t		12t	



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SB性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	76.2	20.0	77.8	19.7	79.8	16.7	81.3	14.8	82.2	12.9
20.0	74.6	20.0	76.1	18.6	78.1	16.1	79.5	14.4	80.2	12.7
22.0	73.0	20.0	74.3	17.7	76.2	15.5	77.6	14.1	78.2	12.5
24.0	71.1	18.8	72.5	16.8	74.3	15.0	75.6	13.9	76.2	12.3
26.0	69.2	17.1	70.7	16.1	72.4	14.6	73.6	13.6	74.1	12.1
28.0	67.2	15.7	68.7	15.0	70.5	14.2	71.6	13.2	72.0	12.0
30.0	65.1	13.5	66.6	13.8	68.4	13.2	69.4	12.8	69.8	11.9
32.0	62.7	11.4	64.4	12.2	66.2	12.2	67.3	11.9	67.4	11.8
34.0	60.5	9.6	62.1	10.3	64.0	11.2	64.9	11.2		
36.0	58.1	7.9	59.7	8.6	61.6	9.4	62.3	9.9		
38.0	55.8	6.5	57.3	7.1	59.0	7.8	59.7	8.2		
40.0	53.3	5.2	54.8	5.7	56.4	6.3	57.0	6.7		
42.0	50.7	4.0	52.2	4.5	53.6	5.0	54.2	5.3		
44.0	48.1	2.9	49.5	3.3	50.8	3.8	51.1	4.0		
46.0					47.8	2.7				
危険角度 (°)	46		47		47		49.5		65.5	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SB性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.6	11.0	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	72.1	11.0	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.6	11.0	74.4	10.6	77.4	9.2	79.9	8.2	81.5	7.1
28.0	69.1	11.0	72.7	10.1	75.7	8.9	78.1	8.0	79.5	7.0
30.0	67.6	11.0	71.0	9.6	74.0	8.6	76.2	7.8	77.6	6.9
32.0	65.9	10.5	69.3	9.2	72.2	8.3	74.4	7.6	75.5	6.8
34.0	64.1	9.9	67.5	8.8	70.4	8.1	72.5	7.5	73.4	6.7
36.0	62.3	9.3	65.7	8.4	68.6	7.8	70.5	7.3	71.3	6.6
38.0	60.4	8.2	63.9	8.1	66.7	7.6	68.5	7.1	69.0	6.6
40.0	58.3	6.9	62.0	7.7	64.7	7.4	66.4	7.0	66.7	6.6
42.0	56.2	5.8	60.0	7.1	62.6	7.2	64.2	6.9		
44.0	54.1	4.7	57.8	5.9	60.4	6.9	61.9	6.8		
46.0	51.9	3.7	55.5	4.8	57.9	5.7	59.4	6.3		
48.0	49.5	2.8	53.1	3.9	55.5	4.7	56.7	5.1		
50.0	47.1	2.0	50.6	3.0	53.0	3.7	53.9	4.0		
52.0			48.0	2.1	50.2	2.7	50.8	3.0		
危険角度 (°)	45		47		47.5		50		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SB性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.5	7.5	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	70.2	7.5	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0	68.8	7.5	73.4	6.7	77.3	5.7	80.4	4.9	82.7	4.4
34.0	67.3	7.4	71.9	6.4	75.7	5.6	78.7	4.8	80.8	4.3
36.0	65.8	6.9	70.3	6.1	74.1	5.4	77.0	4.7	78.9	4.2
38.0	64.2	6.5	68.7	5.8	72.4	5.2	75.2	4.6	77.0	4.2
40.0	62.6	6.1	67.1	5.6	70.7	5.1	73.4	4.5	75.0	4.1
42.0	60.9	5.7	65.4	5.3	68.9	4.9	71.6	4.4	72.9	4.1
44.0	59.2	5.4	63.7	5.0	67.1	4.7	69.7	4.4	70.8	4.0
46.0	57.5	5.1	62.0	4.8	65.3	4.6	67.7	4.3	68.5	4.0
48.0	55.4	4.3	60.2	4.6	63.4	4.4	65.6	4.2	66.2	4.0
50.0	53.3	3.5	58.3	4.4	61.4	4.3	63.5	4.2		
52.0	51.2	2.7	56.1	4.0	59.4	4.2	61.2	4.1		
54.0	49.1	2.0	53.7	3.2	57.3	4.1	58.9	4.1		
56.0	46.9	1.4	51.4	2.4	54.7	3.3	56.2	3.8		
58.0			49.1	1.7	52.0	2.5	53.2	2.9		
60.0					49.4	1.8				
危険角度 (°)	45		47		47.5		51		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SB性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.4	6.5	76.4	6.1	80.7	4.8	84.4	4.0		
32.0	70.1	6.5	75.0	5.9	79.2	4.7	82.8	3.9		
34.0	68.8	6.5	73.6	5.7	77.7	4.5	81.2	3.8	83.7	3.4
36.0	67.3	6.3	72.1	5.5	76.1	4.4	79.5	3.7	81.9	3.3
38.0	65.8	5.9	70.7	5.2	74.6	4.2	77.8	3.6	80.0	3.3
40.0	64.3	5.6	69.1	5.0	73.0	4.1	76.1	3.6	78.1	3.3
42.0	62.7	5.2	67.5	4.7	71.4	4.0	74.3	3.5	76.2	3.2
44.0	61.1	4.9	65.9	4.5	69.7	3.9	72.5	3.4	74.1	3.2
46.0	59.5	4.6	64.3	4.3	68.0	3.8	70.7	3.4	72.0	3.2
48.0	57.8	4.3	62.6	4.1	66.2	3.7	68.8	3.3	69.8	3.2
50.0	56.0	3.9	60.8	3.9	64.4	3.6	66.8	3.3	67.5	3.2
52.0	53.9	3.2	59.0	3.7	62.5	3.6	64.7	3.3		
54.0	51.8	2.5	57.1	3.6	60.5	3.5	62.5	3.2		
56.0	49.7	1.8	54.9	3.1	58.5	3.4	60.2	3.2		
58.0			52.5	2.4	56.3	3.3	57.8	3.2		
60.0			50.2	1.7	53.6	2.6	55.1	3.1		
62.0					50.9	1.9	52.1	2.3		
危険角度 (°)	48		48.5		49		51		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SC性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	76.2	20.0	77.8	19.7	79.8	16.7	81.3	14.8	82.2	12.9
20.0	74.6	20.0	76.1	18.6	78.1	16.1	79.5	14.4	80.2	12.7
22.0	73.0	20.0	74.3	17.7	76.2	15.5	77.6	14.1	78.2	12.5
24.0	71.1	18.8	72.5	16.8	74.3	15.0	75.6	13.9	76.2	12.3
26.0	69.1	16.4	70.7	16.1	72.4	14.6	73.6	13.6	74.1	12.1
28.0	66.9	13.7	68.6	14.7	70.5	14.2	71.6	13.2	72.0	12.0
30.0	64.8	11.5	66.4	12.4	68.4	13.2	69.4	12.8	69.8	11.9
32.0	62.4	9.5	64.1	10.3	66.1	11.3	67.3	11.9	67.4	11.8
34.0	60.2	7.8	61.8	8.5	63.7	9.4	64.7	10.0		
36.0	57.8	6.2	59.4	6.9	61.3	7.7	62.1	8.2		
38.0	55.5	4.9	57.0	5.5	58.7	6.2	59.4	6.6		
40.0	53.0	3.6	54.5	4.2	56.1	4.8	56.8	5.1		
42.0			51.9	3.0	53.3	3.5	53.9	3.8		
危険角度 (°)	50.5		50.5		51		51		65.5	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SC性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.6	11.0	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	72.1	11.0	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.6	11.0	74.4	10.6	77.4	9.2	79.9	8.2	81.5	7.1
28.0	69.1	11.0	72.7	10.1	75.7	8.9	78.1	8.0	79.5	7.0
30.0	67.6	11.0	71.0	9.6	74.0	8.6	76.2	7.8	77.6	6.9
32.0	65.9	10.5	69.3	9.2	72.2	8.3	74.4	7.6	75.5	6.8
34.0	64.1	9.5	67.5	8.8	70.4	8.1	72.5	7.5	73.4	6.7
36.0	62.1	8.0	65.7	8.4	68.6	7.8	70.5	7.3	71.3	6.6
38.0	60.1	6.6	63.9	8.1	66.7	7.6	68.5	7.1	69.0	6.6
40.0	58.0	5.4	61.8	6.9	64.7	7.4	66.4	7.0	66.7	6.6
42.0	55.9	4.3	59.7	5.6	62.5	6.7	64.2	6.9		
44.0	53.7	3.3	57.5	4.5	60.1	5.5	61.8	6.2		
46.0	51.5	2.4	55.2	3.5	57.7	4.4	59.2	5.0		
48.0			52.8	2.6	55.3	3.4	56.5	3.9		
50.0					52.7	2.4	53.6	2.8		
危険角度 (°)	50		50.5		51		51		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SC性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.5	7.5	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	70.2	7.5	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0	68.8	7.5	73.4	6.7	77.3	5.7	80.4	4.9	82.7	4.4
34.0	67.3	7.4	71.9	6.4	75.7	5.6	78.7	4.8	80.8	4.3
36.0	65.8	6.9	70.3	6.1	74.1	5.4	77.0	4.7	78.9	4.2
38.0	64.2	6.5	68.7	5.8	72.4	5.2	75.2	4.6	77.0	4.2
40.0	62.6	6.1	67.1	5.6	70.7	5.1	73.4	4.5	75.0	4.1
42.0	60.9	5.7	65.4	5.3	68.9	4.9	71.6	4.4	72.9	4.1
44.0	59.1	4.8	63.7	5.0	67.1	4.7	69.7	4.4	70.8	4.0
46.0	57.1	3.8	62.0	4.8	65.3	4.6	67.7	4.3	68.5	4.0
48.0	55.1	3.0	60.1	4.5	63.4	4.4	65.6	4.2	66.2	4.0
50.0	52.9	2.2	58.0	3.6	61.4	4.3	63.5	4.2		
52.0	50.8	1.5	55.7	2.8	59.3	3.9	61.2	4.1		
54.0			53.3	2.0	56.9	3.0	58.8	3.6		
56.0			51.1	1.4	54.3	2.2	55.9	2.7		
58.0					51.7	1.5	53.0	1.9		
危険角度 (°)	50		50.5		51		51		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SC性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.4	6.5	76.4	6.1	80.7	4.8	84.4	4.0		
32.0	70.1	6.5	75.0	5.9	79.2	4.7	82.8	3.9		
34.0	68.8	6.5	73.6	5.7	77.7	4.5	81.2	3.8	83.7	3.4
36.0	67.3	6.3	72.1	5.5	76.1	4.4	79.5	3.7	81.9	3.3
38.0	65.8	5.9	70.7	5.2	74.6	4.2	77.8	3.6	80.0	3.3
40.0	64.3	5.6	69.1	5.0	73.0	4.1	76.1	3.6	78.1	3.3
42.0	62.7	5.2	67.5	4.7	71.4	4.0	74.3	3.5	76.2	3.2
44.0	61.1	4.9	65.9	4.5	69.7	3.9	72.5	3.4	74.1	3.2
46.0	59.3	4.3	64.3	4.3	68.0	3.8	70.7	3.4	72.0	3.2
48.0	57.4	3.5	62.6	4.1	66.2	3.7	68.8	3.3	69.8	3.2
50.0	55.4	2.7	60.8	3.9	64.4	3.6	66.8	3.3	67.5	3.2
52.0	53.3	2.0	58.8	3.4	62.5	3.6	64.7	3.3		
54.0	51.3	1.4	56.6	2.7	60.5	3.5	62.5	3.2		
56.0			54.3	2.0	58.3	3.0	60.2	3.2		
58.0			52.0	1.3	55.8	2.3	57.7	2.9		
60.0					53.2	1.6	54.8	2.1		
62.0							51.7	1.3		
危険角度 (°)	50		51		51		51		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SD性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	76.2	20.0	77.8	19.7	79.8	16.7	81.3	14.8	82.2	12.9
20.0	74.6	20.0	76.1	18.6	78.1	16.1	79.5	14.4	80.2	12.7
22.0	72.9	18.8	74.3	17.7	76.2	15.5	77.6	14.1	78.2	12.5
24.0	70.7	15.6	72.5	16.8	74.3	15.0	75.6	13.9	76.2	12.3
26.0	68.6	12.8	70.4	13.9	72.4	14.6	73.6	13.6	74.1	12.1
28.0	66.5	10.4	68.1	11.4	70.3	12.7	71.6	13.2	72.0	12.0
30.0	64.3	8.4	65.9	9.3	68.0	10.4	69.2	11.2	69.7	11.6
32.0	62.0	6.6	63.6	7.4	65.6	8.4	66.8	9.1	67.1	9.4
34.0	59.7	5.1	61.3	5.8	63.3	6.7	64.3	7.3		
36.0	57.4	3.7	59.0	4.3	60.8	5.1	61.7	5.6		
38.0			56.6	3.0	58.2	3.7	59.1	4.2		
40.0					56.4	2.8				
危険角度 (°)	55.5		55.5		56		56		65.5	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SD性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.6	11.0	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	72.1	11.0	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.6	11.0	74.4	10.6	77.4	9.2	79.9	8.2	81.5	7.1
28.0	69.1	11.0	72.7	10.1	75.7	8.9	78.1	8.0	79.5	7.0
30.0	67.4	10.1	71.0	9.6	74.0	8.6	76.2	7.8	77.6	6.9
32.0	65.5	8.4	69.3	9.2	72.2	8.3	74.4	7.6	75.5	6.8
34.0	63.6	6.8	67.5	8.7	70.4	8.1	72.5	7.5	73.4	6.7
36.0	61.6	5.4	65.5	7.1	68.6	7.8	70.5	7.3	71.3	6.6
38.0	59.6	4.2	63.4	5.8	66.6	7.1	68.5	7.1	69.0	6.6
40.0	57.5	3.1	61.3	4.6	64.3	5.8	66.3	6.6	66.7	6.6
42.0	55.4	2.1	59.2	3.5	62.1	4.6	63.9	5.3		
44.0			57.0	2.4	59.7	3.4	61.4	4.1		
46.0					57.3	2.4	58.8	3.0		
危険角度 (°)	54.5		55.5		56		56.5		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SD性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.5	7.5	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	70.2	7.5	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0	68.8	7.5	73.4	6.7	77.3	5.7	80.4	4.9	82.7	4.4
34.0	67.3	7.4	71.9	6.4	75.7	5.6	78.7	4.8	80.8	4.3
36.0	65.8	6.9	70.3	6.1	74.1	5.4	77.0	4.7	78.9	4.2
38.0	64.0	5.7	68.7	5.8	72.4	5.2	75.2	4.6	77.0	4.2
40.0	62.2	4.6	67.1	5.6	70.7	5.1	73.4	4.5	75.0	4.1
42.0	60.3	3.6	65.4	5.3	68.9	4.9	71.6	4.4	72.9	4.1
44.0	58.4	2.7	63.5	4.4	67.1	4.7	69.7	4.4	70.8	4.0
46.0	56.5	1.9	61.4	3.4	65.3	4.6	67.7	4.3	68.5	4.0
48.0			59.4	2.6	63.2	3.8	65.6	4.2	66.2	4.0
50.0			57.3	1.8	61.0	2.9	63.4	3.8		
52.0					58.7	2.1	60.8	2.8		
54.0					56.3	1.3	58.2	1.9		
危険角度 (°)	55		55.5		56		56.5		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SD性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.4	6.5	76.4	6.1	80.7	4.8	84.4	4.0		
32.0	70.1	6.5	75.0	5.9	79.2	4.7	82.8	3.9		
34.0	68.8	6.5	73.6	5.7	77.7	4.5	81.2	3.8	83.7	3.4
36.0	67.3	6.3	72.1	5.5	76.1	4.4	79.5	3.7	81.9	3.3
38.0	65.8	5.9	70.7	5.2	74.6	4.2	77.8	3.6	80.0	3.3
40.0	64.1	5.1	69.1	5.0	73.0	4.1	76.1	3.6	78.1	3.3
42.0	62.3	4.1	67.5	4.7	71.4	4.0	74.3	3.5	76.2	3.2
44.0	60.4	3.2	65.9	4.5	69.7	3.9	72.5	3.4	74.1	3.2
46.0	58.4	2.3	64.2	4.1	68.0	3.8	70.7	3.4	72.0	3.2
48.0	56.5	1.6	62.1	3.2	66.2	3.7	68.8	3.3	69.8	3.2
50.0			60.0	2.4	64.4	3.6	66.8	3.3	67.5	3.2
52.0			57.9	1.7	62.2	2.9	64.7	3.3		
54.0					59.8	2.1	62.4	2.9		
56.0					57.5	1.4	59.8	2.1		
58.0							57.1	1.3		
危険角度 (°)	55		56		56.5		56.5		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SE性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	76.2	20.0	77.8	19.7	79.8	16.7	81.3	14.8	82.2	12.9
20.0	74.6	20.0	76.1	18.6	78.1	16.1	79.5	14.4	80.2	12.7
22.0	72.6	16.3	74.3	17.6	76.2	15.5	77.6	14.1	78.2	12.5
24.0	70.4	13.2	72.2	14.4	74.3	15.0	75.6	13.9	76.2	12.3
26.0	68.3	10.6	70.1	11.7	72.2	13.1	73.6	13.6	74.1	12.1
28.0	66.2	8.4	67.8	9.4	70.0	10.7	71.3	11.6	72.0	12.0
30.0	64.0	6.5	65.6	7.4	67.7	8.5	69.0	9.4	69.5	9.7
32.0	61.7	4.9	63.3	5.7	65.4	6.7	66.6	7.4	66.9	7.7
34.0	59.5	3.4	61.0	4.1	63.0	5.0	64.0	5.6		
36.0			58.7	2.8	60.5	3.6	61.5	4.1		
38.0							58.9	2.7		
危険角度 (°)	57.5		58		58.5		58.5		65.5	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SE性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.6	11.0	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	72.1	11.0	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.6	11.0	74.4	10.6	77.4	9.2	79.9	8.2	81.5	7.1
28.0	69.0	10.1	72.7	10.1	75.7	8.9	78.1	8.0	79.5	7.0
30.0	67.2	8.3	71.0	9.6	74.0	8.6	76.2	7.8	77.6	6.9
32.0	65.3	6.6	69.2	8.6	72.2	8.3	74.4	7.6	75.5	6.8
34.0	63.3	5.2	67.2	7.0	70.4	8.1	72.5	7.5	73.4	6.7
36.0	61.3	3.9	65.2	5.6	68.4	7.0	70.5	7.3	71.3	6.6
38.0	59.3	2.8	63.1	4.3	66.2	5.6	68.4	6.6	69.0	6.6
40.0	57.2	1.7	61.0	3.2	64.0	4.4	66.1	5.3	66.6	5.7
42.0			58.9	2.1	61.8	3.2	63.6	4.0		
44.0					59.5	2.2	61.1	2.8		
危険角度 (°)	56.5		58		58.5		59		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SE性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.5	7.5	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	70.2	7.5	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0	68.8	7.5	73.4	6.7	77.3	5.7	80.4	4.9	82.7	4.4
34.0	67.1	6.6	71.9	6.4	75.7	5.6	78.7	4.8	80.8	4.3
36.0	65.4	5.4	70.3	6.1	74.1	5.4	77.0	4.7	78.9	4.2
38.0	63.6	4.2	68.7	5.8	72.4	5.2	75.2	4.6	77.0	4.2
40.0	61.8	3.2	66.9	5.1	70.7	5.1	73.4	4.5	75.0	4.1
42.0	59.9	2.3	65.0	4.1	68.9	4.9	71.6	4.4	72.9	4.1
44.0	58.0	1.4	63.0	3.1	67.1	4.6	69.7	4.4	70.8	4.0
46.0			61.0	2.2	65.0	3.6	67.7	4.3	68.5	4.0
48.0			58.9	1.4	62.8	2.7	65.4	3.6	66.2	4.0
50.0					60.6	1.8	63.0	2.7		
52.0							60.5	1.8		
危険角度 (°)	56.5		58		58.5		59		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SE性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.4	6.5	76.4	6.1	80.7	4.8	84.4	4.0		
32.0	70.1	6.5	75.0	5.9	79.2	4.7	82.8	3.9		
34.0	68.8	6.5	73.6	5.7	77.7	4.5	81.2	3.8	83.7	3.4
36.0	67.2	5.9	72.1	5.5	76.1	4.4	79.5	3.7	81.9	3.3
38.0	65.3	4.7	70.7	5.2	74.6	4.2	77.8	3.6	80.0	3.3
40.0	63.5	3.7	69.1	5.0	73.0	4.1	76.1	3.6	78.1	3.3
42.0	61.7	2.7	67.5	4.7	71.4	4.0	74.3	3.5	76.2	3.2
44.0	59.8	1.9	65.6	3.8	69.7	3.9	72.5	3.4	74.1	3.2
46.0			63.6	2.9	68.0	3.8	70.7	3.4	72.0	3.2
48.0			61.5	2.1	66.1	3.5	68.8	3.3	69.8	3.2
50.0			59.4	1.3	63.9	2.6	66.8	3.3	67.5	3.2
52.0					61.6	1.8	64.5	2.8		
54.0							62.0	1.9		
危険角度 (°)	58		58.5		59.5		59.5		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SF性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	76.2	20.0	77.8	19.7	79.8	16.7	81.3	14.8	82.2	12.9
20.0	74.3	17.1	76.1	18.5	78.1	16.1	79.5	14.4	80.2	12.7
22.0	72.3	13.7	74.0	14.9	76.2	15.5	77.6	14.1	78.2	12.5
24.0	70.2	10.9	71.9	11.9	74.1	13.2	75.6	13.9	76.2	12.3
26.0	68.0	8.5	69.8	9.6	71.9	10.7	73.4	11.5	74.1	12.0
28.0	65.9	6.4	67.5	7.4	69.7	8.6	71.0	9.3	71.7	9.7
30.0			65.3	5.4	67.4	6.7	68.7	7.4	69.2	7.7
32.0					65.1	4.7	66.2	5.5	66.6	5.8
危険角度 (°)	64		64		64		64		65.5	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SF性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.6	11.0	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	72.1	11.0	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.5	10.0	74.4	10.6	77.4	9.2	79.9	8.2	81.5	7.1
28.0	68.7	8.1	72.7	10.0	75.7	8.9	78.1	8.0	79.5	7.0
30.0	66.9	6.4	70.8	8.3	74.0	8.6	76.2	7.8	77.6	6.9
32.0	64.9	4.6	68.8	6.8	72.2	8.1	74.4	7.6	75.5	6.8
34.0			66.8	5.2	70.1	6.7	72.5	7.5	73.4	6.7
36.0			64.8	3.7	68.0	5.3	70.3	6.3	71.3	6.6
38.0					65.9	3.8	68.1	4.9	68.9	5.5
40.0							65.7	3.5	66.3	3.9
危険角度 (°)	64		64		64		64		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SF性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.5	7.5	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	70.2	7.5	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0	68.5	6.3	73.4	6.7	77.3	5.7	80.4	4.9	82.7	4.4
34.0	66.6	4.7	71.9	6.4	75.7	5.6	78.7	4.8	80.8	4.3
36.0	64.8	3.4	70.2	5.9	74.1	5.4	77.0	4.7	78.9	4.2
38.0			68.3	4.6	72.4	5.2	75.2	4.6	77.0	4.2
40.0			66.4	3.4	70.7	5.1	73.4	4.5	75.0	4.1
42.0					68.6	4.0	71.6	4.4	72.9	4.1
44.0					66.6	2.9	69.6	4.2	70.8	4.0
46.0							67.3	3.0	68.4	3.7
48.0									65.8	2.5
危険角度 (°)	64		64.5		64.5		65		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SF性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.4	6.5	76.4	6.1	80.7	4.8	84.4	4.0		
32.0	70.1	6.5	75.0	5.9	79.2	4.7	82.8	3.9		
34.0	68.4	5.3	73.6	5.7	77.7	4.5	81.2	3.8	83.7	3.4
36.0	66.5	4.0	72.1	5.5	76.1	4.4	79.5	3.7	81.9	3.3
38.0			70.7	5.2	74.6	4.2	77.8	3.6	80.0	3.3
40.0			68.7	4.1	73.0	4.1	76.1	3.6	78.1	3.3
42.0			66.8	3.0	71.4	4.0	74.3	3.5	76.2	3.2
44.0					69.7	3.9	72.5	3.4	74.1	3.2
46.0					67.5	2.8	70.7	3.4	72.0	3.2
48.0							68.7	3.1	69.8	3.2
50.0							66.2	2.1	67.4	2.7
危険角度 (°)	65		65		65.5		65.5		65.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



11.8m — 30m

スーパーラフィングジブ【50mブーム時】

SG性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.7	20.0	79.6	20.0	81.6	17.3	83.2	15.1	84.1	13.2
18.0	75.9	16.9	77.7	18.5	79.8	16.7	81.3	14.8	82.2	12.9
20.0	73.9	13.0	75.6	14.3	78.1	16.0	79.5	14.4	80.2	12.7
22.0	71.8	9.9	73.5	11.1	75.9	12.6	77.5	13.8	78.2	12.5
24.0	69.7	7.3	71.4	8.5	73.7	9.9	75.3	10.9	76.1	11.5
26.0					71.5	7.7	73.0	8.5	73.7	9.0
28.0							70.7	6.5	71.3	6.9
危険角度 (°)	68		69.5		69.5		69.5		70	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SG性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	75.1	11.0	79.0	11.0	82.4	10.4				
22.0	73.5	10.3	77.5	11.0	80.8	9.9	83.4	8.6		
24.0	71.9	8.8	76.0	11.0	79.1	9.6	81.6	8.4	83.4	7.3
26.0	70.1	6.7	74.1	9.1	77.4	9.2	79.9	8.2	81.5	7.1
28.0			72.2	7.3	75.7	8.9	78.1	8.0	79.5	7.0
30.0			70.3	5.5	73.7	7.2	76.2	7.8	77.6	6.9
32.0					71.7	5.8	74.3	6.9	75.5	6.8
34.0							72.1	5.5	73.3	6.1
36.0									71.0	4.5
危険角度 (°)	68.5		69.5		70		70		70	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SG性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0	74.2	7.5	79.1	7.5	83.3	6.5				
26.0	72.8	7.5	77.8	7.5	81.8	6.3				
28.0	71.2	6.2	76.4	7.5	80.3	6.1	83.7	5.1		
30.0	69.5	4.7	74.9	7.1	78.8	5.9	82.1	5.0	84.5	4.4
32.0			73.2	6.1	77.3	5.7	80.4	4.9	82.7	4.4
34.0			71.3	4.6	75.7	5.6	78.7	4.8	80.8	4.3
36.0					74.1	5.4	77.0	4.7	78.9	4.2
38.0					72.0	4.1	75.2	4.6	77.0	4.2
40.0							73.4	4.5	75.0	4.1
42.0							71.2	3.2	72.9	4.1
危険角度 (°)	68.5		69.5		70.5		70.5		71	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SG性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.1	6.5	80.5	6.5						
26.0	73.9	6.5	79.2	6.5	83.6	5.2				
28.0	72.7	6.5	77.8	6.4	82.2	5.0				
30.0	71.0	5.2	76.4	6.1	80.7	4.8	84.4	4.0		
32.0			75.0	5.9	79.2	4.7	82.8	3.9		
34.0			73.5	5.4	77.7	4.5	81.2	3.8	83.7	3.4
36.0			71.6	4.0	76.1	4.4	79.5	3.7	81.9	3.3
38.0					74.6	4.2	77.8	3.6	80.0	3.3
40.0					72.9	3.9	76.1	3.6	78.1	3.3
42.0							74.3	3.5	76.2	3.2
44.0							72.4	3.2	74.1	3.2
46.0									71.9	3.0
危険角度 (°)	69.5		70		71		71		71	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



11.8m — 30m

スーパーラフングジブ【50mブーム時】

SH性能 50mブーム + 1.8m + 11.8mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.7	20.0								
8.0	83.9	20.0								
9.0	83.1	20.0								
10.0	82.3	20.0	84.2	20.0						
11.0	81.6	20.0	83.4	20.0						
12.0	80.8	20.0	82.7	20.0						
14.0	79.3	20.0	81.1	20.0	83.3	18.1				
16.0	77.3	14.7	79.3	16.8	81.6	17.3	83.2	15.1	84.1	13.2
18.0	75.3	10.5	77.1	12.4	79.6	14.3	81.3	14.8	82.2	12.9
20.0			75.0	8.9	77.5	10.8	79.2	12.1	80.2	12.7
22.0					75.4	8.0	77.0	9.1	78.0	9.8
24.0									75.7	7.4
危険角度 (°)	74		74		74		75		75	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SH性能 50mブーム + 1.8m + 19.4mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	11.0								
7.0	84.1	11.0								
8.0	83.4	11.0								
9.0	82.8	11.0								
10.0	82.1	11.0								
11.0	81.4	11.0								
12.0	80.7	11.0	84.7	11.0						
14.0	79.3	11.0	83.3	11.0						
16.0	77.9	11.0	81.9	11.0						
18.0	76.5	11.0	80.4	11.0	84.0	10.8				
20.0	74.8	8.7	79.0	11.0	82.4	10.4				
22.0			77.3	9.3	80.8	9.9	83.4	8.6		
24.0			75.4	7.1	79.0	9.2	81.6	8.4	83.4	7.3
26.0					77.1	7.2	79.9	8.2	81.5	7.1
28.0					75.1	5.6	77.9	6.9	79.5	7.0
30.0							75.8	5.4	77.4	6.1
危険角度 (°)	74		74		74		75		75.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 50mブーム + 1.8m + 27mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.8	7.5								
8.0	84.2	7.5								
9.0	83.6	7.5								
10.0	83.0	7.5								
11.0	82.3	7.5								
12.0	81.7	7.5								
14.0	80.5	7.5								
16.0	79.3	7.5	84.3	7.5						
18.0	78.0	7.5	83.0	7.5						
20.0	76.8	7.5	81.8	7.5						
22.0	75.5	7.5	80.4	7.5	84.7	6.5				
24.0			79.1	7.5	83.3	6.5				
26.0			77.7	7.2	81.8	6.3				
28.0			75.9	5.5	80.3	6.1	83.7	5.1		
30.0					78.8	5.9	82.1	5.0	84.5	4.4
32.0					77.1	5.1	80.4	4.9	82.7	4.4
34.0							78.7	4.8	80.8	4.3
36.0							76.9	4.2	78.9	4.2
38.0									77.0	4.1
危険角度 (°)	74		74.5		75.5		75.5		75.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 50mブーム + 1.8m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.6	6.5								
9.0	84.0	6.5								
10.0	83.4	6.5								
11.0	82.8	6.5								
12.0	82.3	6.5								
14.0	81.1	6.5								
16.0	79.9	6.5								
18.0	78.8	6.5	84.2	6.5						
20.0	77.6	6.5	83.0	6.5						
22.0	76.4	6.5	81.7	6.5						
24.0	75.0	6.0	80.5	6.5						
26.0			79.2	6.5	83.6	5.2				
28.0			77.8	6.2	82.2	5.0				
30.0			76.1	4.7	80.7	4.8	84.4	4.0		
32.0					79.2	4.7	82.8	3.9		
34.0					77.7	4.5	81.2	3.8	83.7	3.4
36.0							79.5	3.7	81.9	3.3
38.0							77.8	3.6	80.0	3.3
40.0									78.1	3.3
危険角度 (°)	74		74.5		76		76		76.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	