



14.4m — 55.0m

メインブーム【通常伸縮】

A1性能

カウンターウエイト 83t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	119.0	117.4	116.5	116.3	70.0	60.0			
8.0	105.1	103.4	102.5	102.3	70.0	60.0	47.0	38.0	
9.0	93.8	92.1	91.2	91.0	70.0	60.0	47.0	38.0	32.0
10.0	84.4	82.7	81.8	81.5	70.0	60.0	47.0	38.0	32.0
11.0	76.5	74.7	73.8	73.6	70.0	60.0	47.0	38.0	32.0
12.0	69.8	68.0	67.0	66.8	68.7	60.0	47.0	38.0	32.0
14.0		57.0	56.0	55.8	57.8	52.6	47.0	38.0	32.0
16.0		47.5	46.4	46.1	48.3	46.5	42.4	38.0	31.0
18.0			38.9	38.7	40.8	41.3	38.1	35.1	27.3
20.0			33.0	32.8	34.8	36.0	34.5	31.1	24.3
22.0				28.1	30.0	31.2	31.1	27.9	21.7
24.0					26.0	27.1	27.8	25.1	19.6
26.0					22.6	23.8	24.4	22.8	17.7
28.0					19.8	20.9	21.5	20.8	16.1
30.0						18.4	19.0	19.0	14.7
32.0						16.2	16.8	17.2	13.4
34.0						14.4	14.9	15.3	12.3
36.0						12.7	13.2	13.6	11.3
38.0							11.7	12.1	10.4
40.0							10.4	10.7	9.6
42.0							9.2	9.5	8.9
44.0								8.4	8.2
46.0								7.4	7.6
48.0									6.7
50.0									5.9
52.0									5.2
危険角度 (°)	—	—	—	—	—	2	3	5	7
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

A2性能

カウンターウエイト 83t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	119.0	117.4	116.5	116.3	70.0	60.0			
8.0	105.1	103.4	102.5	102.3	70.0	60.0	47.0	38.0	
9.0	93.8	92.1	91.2	91.0	70.0	60.0	47.0	38.0	32.0
10.0	84.4	82.7	81.8	81.5	70.0	60.0	47.0	38.0	32.0
11.0	76.5	74.7	73.8	73.6	70.0	60.0	47.0	38.0	32.0
12.0	69.8	68.0	67.0	66.8	68.7	60.0	47.0	38.0	32.0
14.0		57.0	56.0	55.8	57.8	52.6	47.0	38.0	32.0
16.0		47.5	46.4	46.1	48.3	46.5	42.4	38.0	31.0
18.0			38.9	38.7	40.8	41.3	38.1	35.1	27.3
20.0			33.0	32.8	34.8	36.0	34.5	31.1	24.3
22.0				28.1	30.0	31.2	31.1	27.9	21.7
24.0					26.0	27.1	27.8	25.1	19.6
26.0					22.6	23.8	24.4	22.8	17.7
28.0					19.8	20.9	21.5	20.8	16.1
30.0						18.4	19.0	19.0	14.7
32.0						16.2	16.8	17.2	13.4
34.0						14.4	14.9	15.3	12.3
36.0						12.7	13.2	13.6	11.3
38.0							11.7	12.1	10.4
40.0							10.4	10.7	9.6
42.0							9.2	9.5	8.9
44.0								8.4	8.2
46.0								7.4	7.6
48.0									6.7
50.0									5.9
52.0									5.2
危険角度 (°)	—	—	—	—	—	2	3	5	7
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

B1性能

カウンターウエイト 71t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	115.2	113.6	112.7	112.5	70.0	60.0			
8.0	101.7	100.0	99.1	98.9	70.0	60.0	47.0	38.0	
9.0	90.7	89.0	88.1	87.9	70.0	60.0	47.0	38.0	32.0
10.0	81.6	79.8	78.9	78.7	70.0	60.0	47.0	38.0	32.0
11.0	73.9	72.1	71.2	71.0	70.0	60.0	47.0	38.0	32.0
12.0	67.1	65.0	63.9	63.6	65.9	60.0	47.0	38.0	32.0
14.0		52.7	51.6	51.3	53.6	52.6	47.0	38.0	32.0
16.0		43.6	42.5	42.2	44.4	45.6	42.4	38.0	31.0
18.0			35.5	35.2	37.3	38.6	38.1	35.1	27.3
20.0			30.0	29.7	31.7	32.9	33.7	31.1	24.3
22.0				25.3	27.2	28.4	29.1	27.9	21.7
24.0					23.4	24.6	25.3	25.1	19.6
26.0					20.2	21.4	22.1	22.4	17.7
28.0					17.6	18.7	19.3	19.7	16.1
30.0						16.3	17.0	17.3	14.7
32.0						14.3	14.9	15.3	13.4
34.0						12.6	13.1	13.5	12.3
36.0						11.0	11.5	11.9	11.3
38.0							10.1	10.4	10.4
40.0							8.9	9.2	9.4
42.0							7.8	8.0	8.3
44.0								7.0	7.2
46.0								6.1	6.3
48.0									5.4
50.0									4.7
52.0									4.0
危険角度 (°)	—	—	—	—	—	2	3	5	7
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

B2性能

カウンターウエイト 71t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	115.2	113.6	112.7	112.5	70.0	60.0			
8.0	101.7	100.0	99.1	98.9	70.0	60.0	47.0	38.0	
9.0	90.7	89.0	88.1	87.9	70.0	60.0	47.0	38.0	32.0
10.0	81.6	79.8	78.9	78.7	70.0	60.0	47.0	38.0	32.0
11.0	73.9	72.1	71.2	71.0	70.0	60.0	47.0	38.0	32.0
12.0	67.1	65.0	63.9	63.6	65.9	60.0	47.0	38.0	32.0
14.0		52.7	51.6	51.3	53.6	52.6	47.0	38.0	32.0
16.0		43.6	42.5	42.2	44.4	45.6	42.4	38.0	31.0
18.0			35.5	35.2	37.3	38.6	38.1	35.1	27.3
20.0			30.0	29.7	31.7	32.9	33.7	31.1	24.3
22.0				25.3	27.2	28.4	29.1	27.9	21.7
24.0					23.4	24.6	25.3	25.1	19.6
26.0					20.2	21.4	22.1	22.4	17.7
28.0					17.6	18.7	19.3	19.7	16.1
30.0						16.3	17.0	17.3	14.7
32.0						14.3	14.9	15.3	13.4
34.0						12.6	13.1	13.5	12.3
36.0						11.0	11.5	11.9	11.3
38.0							10.1	10.4	10.4
40.0							8.9	9.2	9.4
42.0							7.8	8.0	8.3
44.0								7.0	7.2
46.0								6.1	6.3
48.0									5.4
50.0									4.7
52.0									4.0
危険角度 (°)	—	—	—	—	—	2	3	5	7
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

B3性能

カウンターウエイト 71t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	115.2	113.6	112.7	112.5	70.0	60.0			
8.0	101.7	100.0	99.1	98.9	70.0	60.0	47.0	38.0	
9.0	90.7	89.0	88.1	87.9	70.0	60.0	47.0	38.0	32.0
10.0	81.6	79.8	78.9	78.7	70.0	60.0	47.0	38.0	32.0
11.0	73.9	72.1	71.2	71.0	70.0	60.0	47.0	38.0	32.0
12.0	67.1	65.0	63.9	63.6	65.9	60.0	47.0	38.0	32.0
14.0		50.3	49.4	49.1	51.1	52.2	47.0	38.0	32.0
16.0		40.2	39.3	39.1	40.9	41.9	42.4	38.0	31.0
18.0			32.0	31.8	33.5	34.5	35.1	35.1	27.3
20.0			26.6	26.4	28.0	29.0	29.5	29.8	24.3
22.0				22.2	23.7	24.6	25.2	25.5	21.7
24.0					20.2	21.1	21.7	21.9	19.6
26.0					17.4	18.3	18.8	19.1	17.7
28.0					15.1	15.9	16.4	16.7	16.1
30.0						13.9	14.4	14.6	14.7
32.0						12.2	12.6	12.9	13.1
34.0						10.7	11.1	11.4	11.6
36.0						9.4	9.8	10.0	10.2
38.0							8.6	8.9	9.1
40.0							7.6	7.8	8.0
42.0							6.7	6.9	7.1
44.0								6.1	6.3
46.0								5.2	5.4
48.0									4.5
50.0									3.7
52.0									3.0
危険角度 (°)	—	—	—	—	—	2	3	5	7
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

C1性能

カウンターウエイト 59t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	111.4	109.8	108.9	108.7	70.0	60.0			
8.0	98.3	96.6	95.7	95.5	70.0	60.0	47.0	38.0	
9.0	87.6	85.9	85.0	84.8	70.0	60.0	47.0	38.0	32.0
10.0	78.3	76.2	75.1	74.8	70.0	60.0	47.0	38.0	32.0
11.0	69.3	67.2	66.1	65.8	68.2	60.0	47.0	38.0	32.0
12.0	61.9	59.7	58.7	58.4	60.7	60.0	47.0	38.0	32.0
14.0		48.2	47.1	46.9	49.1	50.4	47.0	38.0	32.0
16.0		39.7	38.6	38.3	40.5	41.8	42.4	38.0	31.0
18.0			32.0	31.8	33.9	35.1	35.9	35.1	27.3
20.0			26.9	26.6	28.6	29.9	30.6	31.0	24.3
22.0				22.5	24.4	25.6	26.3	26.6	21.7
24.0					20.8	22.0	22.7	23.1	19.6
26.0					17.9	19.0	19.7	20.1	17.7
28.0					15.4	16.5	17.1	17.5	16.1
30.0						14.3	14.9	15.3	14.7
32.0						12.4	13.0	13.4	13.4
34.0						10.8	11.3	11.7	11.9
36.0						9.3	9.8	10.2	10.4
38.0							8.5	8.8	9.1
40.0							7.3	7.7	7.9
42.0							6.3	6.6	6.8
44.0								5.6	5.8
46.0								4.8	5.0
48.0									4.2
50.0									3.5
危険角度 (°)	—	—	—	—	—	2	3	5	20
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

C2性能

カウンターウエイト 59t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	111.4	109.8	108.9	108.7	70.0	60.0			
8.0	98.3	96.6	95.7	95.5	70.0	60.0	47.0	38.0	
9.0	87.6	85.9	85.0	84.8	70.0	60.0	47.0	38.0	32.0
10.0	78.3	76.2	75.1	74.8	70.0	60.0	47.0	38.0	32.0
11.0	69.3	67.2	66.1	65.8	68.2	60.0	47.0	38.0	32.0
12.0	61.9	59.7	58.7	58.4	60.7	60.0	47.0	38.0	32.0
14.0		48.2	47.1	46.9	49.1	50.4	47.0	38.0	32.0
16.0		39.7	38.6	38.3	40.5	41.8	42.4	38.0	31.0
18.0			32.0	31.8	33.9	35.1	35.9	35.1	27.3
20.0			26.9	26.6	28.6	29.9	30.6	31.0	24.3
22.0				22.5	24.4	25.6	26.3	26.6	21.7
24.0					20.8	22.0	22.7	23.1	19.6
26.0					17.9	19.0	19.7	20.1	17.7
28.0					15.4	16.5	17.1	17.5	16.1
30.0						14.3	14.9	15.3	14.7
32.0						12.4	13.0	13.4	13.4
34.0						10.8	11.3	11.7	11.9
36.0						9.3	9.8	10.2	10.4
38.0							8.5	8.8	9.1
40.0							7.3	7.7	7.9
42.0							6.3	6.6	6.8
44.0								5.6	5.8
46.0								4.8	5.0
48.0									4.2
50.0									3.4
危険角度 (°)	—	—	—	—	—	2	3	5	20
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

C3性能

カウンターウエイト 59t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	120.0	120.0	120.0	70.0				
7.0	111.4	109.8	108.9	108.7	70.0	60.0			
8.0	98.3	96.6	95.7	95.5	70.0	60.0	47.0	38.0	
9.0	87.6	85.9	85.0	84.8	70.0	60.0	47.0	38.0	32.0
10.0	78.3	76.2	75.1	74.8	70.0	60.0	47.0	38.0	32.0
11.0	68.9	66.9	65.9	65.7	67.9	60.0	47.0	38.0	32.0
12.0	59.3	57.4	56.4	56.2	58.3	59.5	47.0	38.0	32.0
14.0		43.9	43.0	42.8	44.7	45.8	46.5	38.0	32.0
16.0		34.8	33.9	33.7	35.5	36.6	37.2	37.5	31.0
18.0			27.4	27.2	28.9	29.9	30.5	30.8	27.3
20.0			22.5	22.3	24.0	24.9	25.5	25.8	24.3
22.0				18.6	20.1	21.0	21.6	21.9	21.7
24.0					17.0	17.9	18.4	18.7	18.9
26.0					14.4	15.3	15.8	16.1	16.3
28.0					12.4	13.2	13.7	13.9	14.1
30.0						11.4	11.9	12.1	12.3
32.0						9.8	10.4	10.5	10.7
34.0						8.5	8.9	9.2	9.4
36.0						7.4	7.8	8.0	8.2
38.0							6.7	7.0	7.1
40.0							5.7	6.0	6.2
42.0							4.6	4.9	5.2
44.0								4.0	4.2
46.0								3.1	3.4
危険角度 (°)	—	—	—	—	—	2	3	5	30
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

D1性能

カウンターウエイト 41t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	119.8	118.9	118.7	70.0				
7.0	105.6	104.0	103.1	102.9	70.0	60.0			
8.0	91.4	89.3	88.2	87.9	70.0	60.0	47.0	38.0	
9.0	78.7	76.6	75.5	75.3	70.0	60.0	47.0	38.0	32.0
10.0	68.6	66.6	65.5	65.3	67.6	60.0	47.0	38.0	32.0
11.0	60.6	58.5	57.4	57.2	59.5	60.0	47.0	38.0	32.0
12.0	53.9	51.8	50.7	50.5	52.8	54.1	47.0	38.0	32.0
14.0		41.4	40.4	40.1	42.4	43.6	44.4	38.0	32.0
16.0		33.8	32.7	32.5	34.6	35.9	36.7	37.0	31.0
18.0			26.8	26.6	28.7	29.9	30.7	31.0	27.3
20.0			22.2	21.9	23.9	25.2	25.9	26.3	24.3
22.0				18.2	20.1	21.3	22.0	22.4	21.7
24.0					16.9	18.1	18.8	19.2	19.5
26.0					14.3	15.4	16.1	16.5	16.8
28.0					12.1	13.2	13.8	14.2	14.4
30.0						11.2	11.8	12.2	12.4
32.0						9.5	10.1	10.4	10.7
34.0						8.0	8.6	8.9	9.2
36.0						6.7	7.2	7.6	7.8
38.0							6.1	6.4	6.6
40.0							5.0	5.3	5.6
42.0							4.1	4.4	4.6
44.0								3.5	3.7
危険角度 (°)	—	—	—	—	—	2	3	20	32
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

D2性能

カウンターウエイト 41t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	119.8	118.9	118.7	70.0				
7.0	105.6	104.0	103.1	102.9	70.0	60.0			
8.0	91.4	89.3	88.2	87.9	70.0	60.0	47.0	38.0	
9.0	78.7	76.6	75.5	75.3	70.0	60.0	47.0	38.0	32.0
10.0	68.6	66.6	65.5	65.3	67.6	60.0	47.0	38.0	32.0
11.0	60.6	58.5	57.4	57.2	59.5	60.0	47.0	38.0	32.0
12.0	53.9	51.8	50.7	50.5	52.8	54.1	47.0	38.0	32.0
14.0		41.4	40.4	40.1	42.4	43.6	44.4	38.0	32.0
16.0		33.8	32.7	32.5	34.6	35.9	36.7	37.0	31.0
18.0			26.4	26.1	28.1	29.2	29.8	30.2	27.3
20.0			21.4	21.1	22.9	24.0	24.6	25.0	24.3
22.0				17.3	19.0	20.0	20.6	20.9	21.2
24.0					15.8	16.8	17.4	17.7	17.9
26.0					13.2	14.2	14.8	15.1	15.3
28.0					11.1	12.1	12.6	12.9	13.1
30.0						10.2	10.8	11.0	11.3
32.0						8.6	9.2	9.5	9.7
34.0						7.0	7.6	8.0	8.3
36.0						5.6	6.2	6.6	6.8
38.0							4.9	5.3	5.6
40.0							3.8	4.2	4.4
42.0								3.2	3.4
危険角度 (°)	—	—	—	—	—	2	16	29	37
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

D3性能

カウンターウエイト 41t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	119.8	118.9	118.7	70.0				
7.0	105.6	104.0	103.1	102.9	70.0	60.0			
8.0	91.4	89.3	88.2	87.9	70.0	60.0	47.0	38.0	
9.0	78.7	76.6	75.5	75.3	70.0	60.0	47.0	38.0	32.0
10.0	65.8	63.8	62.7	62.5	64.9	60.0	47.0	38.0	32.0
11.0	55.3	53.4	52.4	52.1	54.3	55.6	47.0	38.0	32.0
12.0	47.4	45.5	44.5	44.3	46.4	47.6	47.0	38.0	32.0
14.0		34.3	33.3	33.1	35.1	36.2	36.9	37.2	32.0
16.0		26.8	25.9	25.6	27.5	28.5	29.2	29.5	29.7
18.0			20.5	20.3	22.0	23.0	23.6	23.9	24.1
20.0			16.5	16.2	17.9	18.9	19.4	19.7	19.9
22.0				13.1	14.7	15.6	16.2	16.4	16.7
24.0					12.1	13.0	13.5	13.8	14.0
26.0					10.0	10.9	11.4	11.7	11.9
28.0					8.3	9.1	9.6	9.9	10.1
30.0						7.6	8.1	8.3	8.5
32.0						6.3	6.8	7.0	7.2
34.0						4.8	5.5	5.8	6.1
36.0						3.6	4.2	4.5	4.8
38.0							3.1	3.4	3.7
危険角度 (°)	—	—	—	—	—	2	28	37	44
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

D4性能

カウンターウエイト 41t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	120.0	119.8	118.9	118.7	70.0				
7.0	105.6	103.3	102.0	101.7	70.0	60.0			
8.0	81.3	79.2	78.0	77.8	70.0	60.0	47.0	38.0	
9.0	65.4	63.4	62.3	62.1	64.4	60.0	47.0	38.0	32.0
10.0	54.1	52.2	51.2	51.0	53.2	54.4	47.0	38.0	32.0
11.0	45.8	44.0	43.0	42.8	44.9	46.0	46.8	38.0	32.0
12.0	39.4	37.6	36.7	36.4	38.4	39.6	40.3	38.0	32.0
14.0		28.4	27.5	27.3	29.1	30.2	30.8	31.2	31.4
16.0		22.1	21.2	21.0	22.7	23.8	24.4	24.7	24.9
18.0			16.6	16.4	18.1	19.1	19.7	19.9	20.2
20.0			13.2	13.0	14.6	15.5	16.1	16.3	16.6
22.0				10.3	11.8	12.7	13.2	13.5	13.7
24.0					9.5	10.4	11.0	11.2	11.4
26.0					7.7	8.6	9.1	9.3	9.5
28.0					6.0	7.0	7.5	7.8	8.0
30.0						5.5	6.1	6.4	6.6
32.0						4.0	4.6	5.0	5.3
34.0							3.3	3.7	4.0
危険角度 (°)	—	—	—	—	—	33	38	45	50
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

E1性能

カウンターウエイト 31t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	117.2	115.6	114.8	114.6	70.0				
7.0	99.5	97.5	96.3	96.1	70.0	60.0			
8.0	84.0	82.0	80.9	80.6	70.0	60.0	47.0	38.0	
9.0	72.2	70.2	69.1	68.8	70.0	60.0	47.0	38.0	32.0
10.0	62.9	60.8	59.7	59.5	61.9	60.0	47.0	38.0	32.0
11.0	55.3	53.3	52.2	51.9	54.3	55.6	47.0	38.0	32.0
12.0	49.1	47.0	46.0	45.7	48.0	49.3	47.0	38.0	32.0
14.0		37.4	36.3	36.1	38.3	39.6	40.4	38.0	32.0
16.0		30.2	29.2	28.9	31.1	32.3	33.1	33.5	31.0
18.0			23.7	23.4	25.5	26.8	27.5	27.9	27.3
20.0			19.4	19.1	21.1	22.4	23.1	23.5	23.7
22.0				15.6	17.6	18.8	19.5	19.8	20.1
24.0					14.6	15.8	16.5	16.8	17.1
26.0					12.1	13.3	14.0	14.3	14.6
28.0					10.1	11.2	11.8	12.2	12.4
30.0						9.3	10.0	10.3	10.6
32.0						7.8	8.4	8.7	9.0
34.0						6.3	6.9	7.3	7.5
36.0						5.0	5.6	5.9	6.2
38.0							4.3	4.7	5.0
40.0							3.2	3.6	3.9
危険角度 (°)	—	—	—	—	—	2	20	33	40
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

E2性能

カウンターウエイト 31t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	117.2	115.6	114.8	114.6	70.0				
7.0	99.5	97.5	96.3	96.1	70.0	60.0			
8.0	84.0	82.0	80.9	80.6	70.0	60.0	47.0	38.0	
9.0	72.2	70.2	69.1	68.8	70.0	60.0	47.0	38.0	32.0
10.0	62.9	60.8	59.7	59.5	61.9	60.0	47.0	38.0	32.0
11.0	55.3	53.3	52.2	51.9	54.3	55.6	47.0	38.0	32.0
12.0	49.1	47.0	46.0	45.7	48.0	49.3	47.0	38.0	32.0
14.0		37.0	35.9	35.7	37.9	39.2	39.9	38.0	32.0
16.0		28.5	27.5	27.3	29.4	30.5	31.2	31.6	31.0
18.0			21.6	21.4	23.3	24.4	25.1	25.4	25.7
20.0			17.2	17.0	18.8	19.8	20.5	20.8	21.0
22.0				13.6	15.3	16.3	16.9	17.2	17.5
24.0					12.5	13.5	14.1	14.4	14.6
26.0					10.2	11.2	11.8	12.1	12.3
28.0					8.1	9.3	9.8	10.1	10.3
30.0						7.4	8.1	8.5	8.7
32.0						5.7	6.4	6.8	7.1
34.0						4.3	4.9	5.3	5.6
36.0						3.1	3.7	4.0	4.3
38.0									3.2
危険角度 (°)	—	—	—	—	—	15	33	40	44
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

E3性能

カウンターウエイト 31t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	117.2	115.6	114.8	114.6	70.0				
7.0	99.5	97.5	96.3	96.1	70.0	60.0			
8.0	84.0	82.0	80.9	80.6	70.0	60.0	47.0	38.0	
9.0	69.4	67.2	66.0	65.8	68.4	60.0	47.0	38.0	32.0
10.0	56.6	54.6	53.5	53.3	55.6	57.0	47.0	38.0	32.0
11.0	47.4	45.4	44.4	44.2	46.4	47.7	47.0	38.0	32.0
12.0	40.3	38.5	37.5	37.3	39.4	40.6	41.3	38.0	32.0
14.0		28.6	27.7	27.5	29.5	30.6	31.2	31.6	31.8
16.0		22.0	21.1	20.9	22.8	23.8	24.5	24.8	25.0
18.0			16.4	16.2	17.9	18.9	19.5	19.9	20.1
20.0			12.9	12.7	14.3	15.3	15.9	16.2	16.4
22.0				10.0	11.5	12.4	13.0	13.3	13.5
24.0					9.2	10.1	10.7	10.9	11.2
26.0					7.4	8.3	8.8	9.1	9.3
28.0					5.5	6.7	7.2	7.5	7.7
30.0						5.1	5.7	6.1	6.3
32.0						3.6	4.2	4.6	4.9
34.0								3.3	3.6
危険角度 (°)	—	—	—	—	—	33	41	45	50
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

E4性能

カウンターウエイト 31t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	117.2	115.6	114.8	114.6	70.0				
7.0	91.2	88.8	87.5	87.3	70.0	60.0			
8.0	69.9	67.7	66.6	66.4	68.9	60.0	47.0	38.0	
9.0	55.9	53.9	52.9	52.6	55.0	56.3	47.0	38.0	32.0
10.0	46.0	44.2	43.2	43.0	45.2	46.4	47.0	38.0	32.0
11.0	38.7	36.9	36.0	35.8	37.9	39.0	39.8	38.0	32.0
12.0	33.1	31.3	30.4	30.2	32.2	33.3	34.0	34.4	32.0
14.0		23.3	22.4	22.2	24.1	25.1	25.8	26.1	26.3
16.0		17.8	16.9	16.7	18.5	19.5	20.1	20.4	20.6
18.0			12.9	12.7	14.4	15.4	16.0	16.2	16.5
20.0			9.9	9.7	11.3	12.2	12.8	13.1	13.3
22.0				7.3	8.9	9.8	10.3	10.6	10.8
24.0					6.9	7.8	8.3	8.6	8.8
26.0					4.8	6.1	6.7	6.9	7.1
28.0					3.1	4.3	5.0	5.4	5.7
30.0							3.5	3.9	4.2
危険角度 (°)	—	—	—	—	20	43	46	51	55
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

F1性能

カウンターウエイト 21t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	110.7	108.6	107.4	107.2	70.0				
7.0	91.1	89.0	87.9	87.6	70.0	60.0			
8.0	76.7	74.7	73.6	73.3	70.0	60.0	47.0	38.0	
9.0	65.7	63.7	62.6	62.4	64.8	60.0	47.0	38.0	32.0
10.0	57.1	55.1	54.0	53.7	56.1	57.4	47.0	38.0	32.0
11.0	50.1	48.1	47.0	46.7	49.1	50.4	47.0	38.0	32.0
12.0	44.3	42.3	41.2	41.0	43.3	44.6	45.4	38.0	32.0
14.0		33.3	32.2	32.0	34.2	35.5	36.3	36.7	32.0
16.0		26.7	25.6	25.4	27.6	28.8	29.6	30.0	30.2
18.0			20.5	20.3	22.4	23.6	24.3	24.7	24.9
20.0			16.3	16.0	17.9	19.0	19.7	20.0	20.2
22.0				12.7	14.4	15.5	16.1	16.4	16.7
24.0					11.6	12.7	13.3	13.6	13.8
26.0					9.3	10.4	11.0	11.3	11.5
28.0					7.1	8.4	9.1	9.4	9.6
30.0						6.5	7.2	7.6	7.9
32.0						4.9	5.5	5.9	6.2
34.0						3.5	4.1	4.5	4.8
36.0								3.3	3.5
危険角度 (°)	—	—	—	—	—	27	37	41	47
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

F2性能

カウンターウエイト 21t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	110.7	108.6	107.4	107.2	70.0				
7.0	91.1	89.0	87.9	87.6	70.0	60.0			
8.0	76.7	74.7	73.6	73.3	70.0	60.0	47.0	38.0	
9.0	65.7	63.7	62.6	62.4	64.8	60.0	47.0	38.0	32.0
10.0	57.1	55.1	54.0	53.7	56.1	57.4	47.0	38.0	32.0
11.0	50.1	48.1	47.0	46.7	49.1	50.4	47.0	38.0	32.0
12.0	43.6	41.4	40.3	40.0	42.4	43.8	44.6	38.0	32.0
14.0		30.3	29.3	29.0	31.2	32.5	33.2	33.6	32.0
16.0		23.0	22.0	21.8	23.8	25.0	25.7	26.0	26.3
18.0			16.8	16.6	18.5	19.6	20.3	20.7	20.9
20.0			13.0	12.8	14.6	15.7	16.3	16.6	16.9
22.0				9.7	11.6	12.6	13.2	13.5	13.8
24.0					9.0	10.2	10.8	11.1	11.3
26.0					6.6	8.0	8.7	9.0	9.3
28.0					4.7	6.0	6.7	7.1	7.4
30.0						4.3	5.0	5.4	5.7
32.0							3.5	3.9	4.2
危険角度 (°)	—	—	—	—	—	38	42	48	52
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

F3性能

カウンターウエイト 21t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	110.7	108.6	107.4	107.2	70.0				
7.0	91.1	89.0	87.9	87.6	70.0	60.0			
8.0	74.6	72.3	71.0	70.7	70.0	60.0	47.0	38.0	
9.0	58.4	56.3	55.1	54.9	57.4	58.9	47.0	38.0	32.0
10.0	47.7	45.4	44.3	44.1	46.4	47.8	47.0	38.0	32.0
11.0	39.4	37.5	36.5	36.2	38.5	39.7	40.5	38.0	32.0
12.0	33.4	31.5	30.5	30.3	32.4	33.6	34.3	34.7	32.0
14.0		23.0	22.1	21.9	23.8	24.9	25.6	25.9	26.2
16.0		17.3	16.4	16.2	18.0	19.1	19.7	20.0	20.3
18.0			12.4	12.2	13.9	14.9	15.5	15.8	16.0
20.0			9.3	9.1	10.8	11.7	12.3	12.6	12.8
22.0				6.5	8.3	9.3	9.8	10.1	10.3
24.0					6.2	7.3	7.8	8.1	8.3
26.0					4.1	5.4	6.1	6.4	6.7
28.0						3.7	4.4	4.8	5.1
30.0								3.2	3.5
危険角度 (°)	—	—	—	—	30	43	49	51	55
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

F4性能

カウンターウエイト 21t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	108.3	105.5	104.0	102.5	70.0				
7.0	76.8	74.5	73.2	72.9	70.0	60.0			
8.0	58.5	56.4	55.2	55.0	57.5	57.4	47.0	38.0	
9.0	46.5	44.5	43.5	43.2	45.6	46.9	47.0	38.0	32.0
10.0	38.0	36.2	35.2	34.9	37.1	38.4	39.1	38.0	32.0
11.0	31.8	29.9	29.0	28.8	30.8	32.0	32.7	33.1	32.0
12.0	26.9	25.1	24.2	24.0	26.0	27.1	27.8	28.2	28.4
14.0		18.2	17.3	17.1	19.0	20.1	20.7	21.0	21.3
16.0		13.5	12.6	12.5	14.2	15.2	15.8	16.1	16.4
18.0			9.2	9.0	10.7	11.7	12.3	12.6	12.8
20.0			6.4	6.1	8.0	9.0	9.5	9.8	10.0
22.0					5.7	6.9	7.4	7.7	7.9
24.0					3.5	4.8	5.5	5.9	6.2
26.0						3.0	3.7	4.1	4.4
危険角度 (°)	—	—	—	25	38	47	53	57	60
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

F5性能

カウンターウエイト 21t アウトリガー張出 5.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	111.8	109.2	107.6	105.0	70.0				
6.0	74.8	72.6	71.4	71.1	70.0				
7.0	54.9	53.0	51.9	51.7	54.0	54.9			
8.0	42.6	40.8	39.8	39.6	41.7	43.0	43.7	38.0	
9.0	34.2	32.5	31.5	31.3	33.4	34.5	35.2	35.5	32.0
10.0	28.1	26.4	25.6	25.4	27.3	28.3	29.0	29.3	29.6
11.0	23.4	21.9	21.0	20.8	22.6	23.7	24.3	24.6	24.9
12.0	19.8	18.3	17.4	17.3	19.0	20.0	20.6	20.9	21.2
14.0		13.0	12.2	12.0	13.7	14.7	15.2	15.5	15.7
16.0		9.4	8.6	8.4	10.0	10.9	11.5	11.7	11.9
18.0			5.9	5.7	7.2	8.1	8.7	8.9	9.1
20.0					5.1	6.0	6.5	6.8	7.0
22.0						4.1	4.8	5.1	5.3
危険角度 (°)	—	—	35	39	49	55	59	62	65
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

G1性能

カウンターウエイト 11t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	100.8	98.7	97.5	97.3	70.0				
7.0	82.7	80.6	79.5	79.2	70.0	60.0			
8.0	69.4	67.4	66.3	66.0	68.5	60.0	47.0	38.0	
9.0	59.3	57.3	56.2	55.9	58.4	59.7	47.0	38.0	32.0
10.0	51.3	49.3	48.2	48.0	50.3	51.7	47.0	38.0	32.0
11.0	44.9	42.8	41.8	41.5	43.9	45.2	46.0	38.0	32.0
12.0	39.6	37.5	36.5	36.2	38.5	39.8	40.6	38.0	32.0
14.0		29.1	28.0	27.7	30.0	31.4	32.2	32.6	32.0
16.0		21.7	20.6	20.4	22.5	23.7	24.5	24.8	25.1
18.0			15.5	15.3	17.2	18.4	19.1	19.4	19.7
20.0			11.7	11.5	13.4	14.5	15.1	15.5	15.7
22.0				8.2	10.4	11.5	12.1	12.4	12.6
24.0					7.7	9.1	9.7	10.0	10.2
26.0					5.3	6.7	7.5	7.9	8.2
28.0					3.5	4.8	5.5	5.9	6.2
30.0						3.1	3.8	4.2	4.6
32.0									3.1
危険角度 (°)	—	—	—	—	10	38	45	50	52
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

G2性能

カウンターウエイト 11t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	100.8	98.7	97.5	97.3	70.0				
7.0	82.7	80.6	79.5	79.2	70.0	60.0			
8.0	69.4	67.4	66.3	66.0	68.5	60.0	47.0	38.0	
9.0	59.3	57.3	56.2	55.9	58.4	59.3	47.0	38.0	32.0
10.0	51.3	48.9	47.6	47.4	50.1	49.7	47.0	38.0	32.0
11.0	42.0	39.8	38.6	38.3	40.9	42.3	41.6	38.0	32.0
12.0	35.1	33.0	31.9	31.6	34.0	35.4	36.0	35.1	32.0
14.0		23.6	22.5	22.3	24.5	25.8	26.5	26.9	26.4
16.0		17.4	16.4	16.2	18.2	19.4	20.1	20.5	20.7
18.0			12.1	11.9	13.8	14.9	15.6	15.9	16.1
20.0			8.5	8.2	10.4	11.5	12.2	12.5	12.7
22.0				5.2	7.5	8.9	9.5	9.8	10.1
24.0					5.0	6.4	7.1	7.6	7.9
26.0					3.0	4.3	5.0	5.5	5.8
28.0							3.3	3.7	4.0
危険角度 (°)	—	—	—	—	30	47	50	54	58
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

G3性能

カウンターウエイト 11t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	120.0	120.0	70.0				
6.0	100.8	98.7	97.5	97.3	70.0				
7.0	82.7	80.3	78.9	78.5	70.0	60.0			
8.0	61.1	58.8	57.5	57.2	60.0	57.7	47.0	38.0	
9.0	47.5	45.3	44.2	43.9	46.5	47.7	46.5	38.0	32.0
10.0	38.2	36.2	35.1	34.9	37.2	38.6	39.3	38.0	32.0
11.0	31.5	29.5	28.5	28.3	30.5	31.8	32.5	32.8	31.9
12.0	26.4	24.5	23.5	23.3	25.4	26.6	27.3	27.7	27.7
14.0		17.4	16.4	16.2	18.2	19.3	20.0	20.3	20.6
16.0		12.6	11.7	11.5	13.3	14.4	15.0	15.3	15.6
18.0			8.3	8.1	9.8	10.8	11.4	11.7	12.0
20.0					7.2	8.2	8.7	9.0	9.3
22.0					4.6	6.0	6.6	6.9	7.1
24.0						3.8	4.5	5.0	5.3
危険角度 (°)	—	—	35	39	43	51	56	58	62
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

G4性能

カウンターウエイト 11t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	120.0	120.0	118.3	115.0	70.0				
6.0	88.8	86.0	84.1	82.1	70.0				
7.0	62.4	60.1	58.8	58.5	59.6	55.8			
8.0	47.1	45.0	43.8	43.6	46.1	45.4	44.1	38.0	
9.0	37.1	35.1	34.0	33.8	36.1	37.4	36.8	35.6	32.0
10.0	30.0	28.1	27.1	26.9	29.1	30.3	31.1	30.2	29.3
11.0	24.7	22.9	22.0	21.8	23.8	25.0	25.7	25.8	25.2
12.0	20.7	18.9	18.0	17.8	19.8	20.9	21.6	21.9	21.7
14.0		13.2	12.3	12.1	13.9	15.0	15.6	16.0	16.2
16.0		9.2	8.4	8.2	9.9	10.9	11.6	11.9	12.1
18.0					7.0	8.0	8.6	8.9	9.1
20.0					4.2	5.5	6.3	6.6	6.8
22.0						3.2			
危険角度 (°)	—	—	42	45	48	55	60	64	67
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

G5性能

カウンターウエイト 11t アウトリガー張出 5.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	119.1	114.6	102.7	99.8					
5.0	90.9	88.3	85.4	83.2	70.0				
6.0	60.2	58.0	56.8	56.5	57.8				
7.0	43.7	41.8	40.7	40.5	42.8	42.7			
8.0	33.5	31.7	30.7	30.5	32.7	33.9	34.0	32.8	
9.0	26.5	24.8	23.9	23.7	25.7	26.9	27.6	27.4	26.5
10.0	21.5	19.9	19.0	18.8	20.7	21.8	22.4	22.7	22.4
11.0	17.6	16.1	15.2	15.0	16.8	17.9	18.5	18.8	19.0
12.0	14.7	13.1	12.3	12.1	13.8	14.8	15.5	15.8	16.0
14.0		8.7	8.0	7.8	9.4	10.4	11.0	11.3	11.5
16.0		5.7			6.4	7.3	7.8	8.1	8.3
18.0					3.6	5.0	5.5	5.8	
危険角度 (°)	—	—	50	52	53	61	65	68	71
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

H1性能

カウンターウエイト 0t アウトリガー張出 9.4m (全周)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	114.1	111.9	110.8	110.5	70.0				
6.0	90.2	88.2	87.1	86.8	70.0				
7.0	73.8	71.7	70.6	70.4	70.0	60.0			
8.0	61.7	59.7	58.6	58.4	60.8	60.0	47.0	38.0	
9.0	52.5	50.5	49.4	49.2	51.6	52.9	47.0	38.0	32.0
10.0	45.2	43.2	42.2	41.9	44.3	45.6	45.3	38.0	32.0
11.0	39.3	37.3	36.0	35.7	38.4	38.9	38.2	37.1	32.0
12.0	32.7	30.4	29.2	28.9	31.5	33.0	32.7	31.8	31.0
14.0		21.0	19.9	19.7	22.0	23.3	24.1	23.9	23.4
16.0		15.1	14.0	13.8	15.9	17.1	17.9	18.2	18.0
18.0			9.7	9.4	11.6	12.8	13.5	13.8	13.9
20.0			6.0	5.7	8.2	9.6	10.2	10.6	10.8
22.0					5.3	6.7	7.5	8.0	8.2
24.0						4.3	5.1	5.6	5.9
26.0							3.2	3.6	3.9
危険角度 (°)	—	—	—	28	42	50	52	57	62
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

H2性能

カウンターウエイト 0t アウトリガー張出 8.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	114.1	111.9	110.8	110.5	70.0				
6.0	90.2	88.2	87.1	86.8	70.0				
7.0	73.8	71.7	70.6	70.4	70.0	60.0			
8.0	61.7	59.7	58.6	58.4	58.6	55.1	47.0	38.0	
9.0	49.6	47.1	45.7	45.4	46.8	44.7	43.6	38.0	32.0
10.0	39.0	36.7	35.4	35.1	37.9	37.0	36.3	35.2	32.0
11.0	31.6	28.3	28.2	27.9	30.5	31.0	30.6	29.8	28.9
12.0	26.1	23.9	22.8	22.5	24.9	26.2	26.1	25.5	24.8
14.0		16.4	15.3	15.1	17.3	18.5	19.2	18.9	18.5
16.0		11.4	10.4	10.1	12.2	13.4	14.1	14.2	14.0
18.0			6.1	5.8	8.4	9.8	10.4	10.6	10.5
20.0					5.1	6.6	7.4	7.8	7.8
22.0						4.0	4.8	5.3	5.6
危険角度 (°)	—	—	34	38	48	54	59	62	66
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)



14.4m — 55.0m

メインブーム【通常伸縮】

H3性能

カウンターウエイト 0t アウトリガー張出 7.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	120.0	120.0					
5.0	114.1	111.9	110.8	110.5	70.0				
6.0	90.2	88.2	85.1	82.8	70.0				
7.0	64.1	61.4	59.9	59.6	57.8	53.8			
8.0	46.6	44.2	43.0	42.7	45.2	42.9	41.6	38.0	
9.0	35.7	33.6	32.4	32.1	34.7	34.8	34.1	33.0	31.8
10.0	28.3	26.3	25.2	24.9	27.3	28.6	28.4	27.6	26.7
11.0	22.9	21.0	20.0	19.7	21.9	23.2	23.8	23.2	22.6
12.0	18.9	17.0	16.0	15.8	17.9	19.1	19.8	19.7	19.2
14.0		11.3	10.4	10.2	12.1	13.2	13.9	14.2	14.0
16.0		7.5	6.3	6.1	8.2	9.3	9.9	10.2	10.2
18.0					5.0	6.5	7.1	7.3	7.3
20.0							4.5		
危険角度 (°)	—	—	43	46	53	60	63	67	70
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

H4性能

カウンターウエイト 0t アウトリガー張出 6.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	120.0	120.0	120.0					
4.5	120.0	120.0	110.0	106.5					
5.0	111.7	99.7	88.6	86.0	70.0				
6.0	67.8	65.0	61.8	60.1	56.9				
7.0	47.0	44.6	43.3	43.1	43.3	40.7			
8.0	34.9	32.7	31.6	31.3	33.9	32.4	31.7	30.5	
9.0	26.9	25.0	23.9	23.7	26.0	26.2	25.9	25.0	24.2
10.0	21.3	19.5	18.5	18.2	20.4	21.5	21.3	20.8	20.1
11.0	17.2	15.4	14.4	14.2	16.3	17.5	17.7	17.3	16.8
12.0	14.0	12.3	11.3	11.1	13.1	14.2	14.7	14.4	14.1
14.0		7.7	6.6	6.4	8.5	9.6	10.1	10.0	9.8
16.0					4.9	6.3	6.7	6.7	
危険角度 (°)	—	35	50	52	57	65	68	71	74
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)

H5性能

カウンターウエイト 0t アウトリガー張出 5.4m (側方)

作業半径 (m)	14.4m ブーム	19.55m ブーム	23.6m ブーム	24.7m ブーム	32.0m ブーム	40.0m ブーム	45.0m ブーム	50.0m ブーム	55.0m ブーム
3.0	120.0								
3.5	120.0	120.0							
4.0	120.0	107.0	93.6	90.5					
4.5	90.4	84.7	74.9	72.6					
5.0	68.4	65.8	61.6	59.8	55.7				
6.0	44.5	42.3	41.1	40.8	41.0				
7.0	31.7	29.8	28.7	28.5	30.8	29.7			
8.0	23.7	21.9	21.0	20.7	22.9	23.4	23.1	22.2	
9.0	18.3	16.6	15.7	15.5	17.5	18.6	18.6	18.0	17.4
10.0	14.4	12.8	11.9	11.7	13.6	14.7	15.0	14.7	14.2
11.0	11.4	9.8	9.0	8.8	10.6	11.7	12.2	11.9	11.6
12.0	9.1	7.5	6.7	6.5	8.3	9.3	9.8	9.6	9.4
危険角度 (°)	—	47	56	58	64	70	73	76	77
フック種類	120t	120t	120t	120t	83t	83t	83t	83t	83t
フック質量 (t)	1.90	1.90	1.90	1.90	1.0	1.0	1.0	1.0	1.0
巻掛本数	12	12	12	12	7	6	4	4	4

(単位 : ton)