



13.6m — 50.0m

ブームロックピン無し

AS性能 C/W 100t O/R 9.2m C/S使用 ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	102.0	92.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	102.0	87.2	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	95.9	82.4	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	60.5
14.0		29.5	36.0	41.4	39.4	44.1	47.8	51.5	54.1
16.0		23.5	32.5	37.2	34.7	39.3	42.7	45.9	49.0
18.0			18.8	32.9	31.0	35.3	38.2	41.7	44.7
20.0			15.0	27.2	27.9	31.9	34.4	37.7	40.5
22.0				13.6	25.2	29.0	31.1	34.3	36.6
24.0				10.7	20.6	25.7	28.2	31.4	33.3
26.0					16.0	22.0	25.7	28.8	30.5
28.0					11.1	18.1	22.7	26.3	28.0
30.0						7.7	19.4	23.5	25.9
32.0						5.9	15.3	20.3	23.6
34.0						4.2	11.5	17.1	21.0
36.0							4.5	13.8	18.3
38.0								10.6	15.5
40.0									12.6
42.0									9.7
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

A1性能 C/W 100t O/R 9.2m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	102.0	92.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	102.0	87.2	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	94.5	82.4	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	60.5
14.0		29.5	36.0	41.4	39.4	44.1	47.8	51.5	54.1
16.0		23.5	32.5	37.2	34.7	39.3	42.7	45.9	49.0
18.0			18.8	32.9	31.0	35.3	38.2	41.7	44.7
20.0			15.0	27.2	27.9	31.9	34.4	37.7	40.5
22.0				13.6	25.2	29.0	31.1	34.3	36.6
24.0				10.7	20.6	25.7	28.2	31.4	33.3
26.0					16.0	22.0	25.7	28.8	30.5
28.0					11.1	18.1	22.7	26.3	28.0
30.0						7.7	19.4	23.5	25.9
32.0						5.9	15.3	20.3	23.6
34.0						4.2	11.5	17.1	21.0
36.0							4.5	13.8	18.3
38.0								10.6	15.5
40.0									12.6
42.0									9.7
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

A2性能 C/W 100t O/R 8.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	102.0	92.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	102.0	87.2	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	94.5	82.4	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	60.5
14.0		29.5	36.0	41.4	39.4	44.1	47.8	51.5	54.1
16.0		23.5	32.5	37.2	34.7	39.3	42.7	45.9	49.0
18.0			18.8	32.9	31.0	35.3	38.2	41.7	44.7
20.0			15.0	27.2	27.9	31.9	34.4	37.7	40.5
22.0				13.6	25.2	29.0	31.1	34.3	36.6
24.0				10.7	20.6	25.7	28.2	31.4	33.3
26.0					16.0	22.0	25.7	28.8	30.5
28.0					11.1	18.1	22.7	26.3	28.0
30.0						7.7	19.4	23.5	25.9
32.0						5.9	15.3	20.3	23.6
34.0						4.2	11.5	17.1	21.0
36.0							4.5	13.8	18.3
38.0								10.6	15.5
40.0									12.6
42.0									9.7
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

B1性能 C/W 60t O/R 9.2m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	95.0	92.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	85.4	84.2	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	77.4	76.1	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	60.5
14.0		29.5	36.0	41.4	39.4	44.1	47.8	51.5	54.1
16.0		23.5	32.5	37.2	34.7	39.3	42.7	45.9	49.0
18.0			18.8	32.9	31.0	35.3	38.2	41.7	43.7
20.0			15.0	27.2	27.9	31.9	34.4	36.8	37.5
22.0				13.6	25.2	29.0	30.3	31.5	32.2
24.0				10.7	20.6	25.3	26.0	27.1	27.8
26.0					16.0	21.8	22.4	23.6	24.3
28.0					11.1	18.1	19.5	20.6	21.3
30.0						7.7	17.1	18.1	18.8
32.0						5.9	15.0	16.0	16.7
34.0						4.2	11.5	14.2	14.9
36.0							4.5	12.7	13.3
38.0								10.6	11.9
40.0									10.7
42.0									9.6
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

B2性能 C/W 60t O/R 8.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	95.0	92.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	85.4	84.2	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	77.4	76.1	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	60.5
14.0		29.5	36.0	41.4	39.4	44.1	47.8	51.5	54.1
16.0		23.5	32.5	37.2	34.7	39.3	42.7	45.9	49.0
18.0			18.8	32.9	31.0	35.3	38.2	39.6	40.3
20.0			15.0	27.2	27.9	31.3	31.9	33.2	33.9
22.0				13.6	25.2	26.4	27.0	28.2	28.9
24.0				10.7	20.6	22.5	23.1	24.2	24.9
26.0					16.0	19.3	19.9	21.0	21.7
28.0					11.1	16.7	17.2	18.3	19.0
30.0						7.7	15.0	16.1	16.7
32.0						5.9	13.1	14.1	14.8
34.0						4.2	11.5	12.5	13.1
36.0							4.5	11.0	11.6
38.0								9.8	10.4
40.0									9.3
42.0									8.3
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

B3性能 C/W 60t O/R 7.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	95.0	92.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	83.1	81.6	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	70.1	68.7	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	60.5
14.0		29.5	36.0	41.4	39.4	44.1	47.0	48.3	49.0
16.0		23.5	32.5	35.4	34.7	36.9	37.5	38.7	39.4
18.0			18.8	28.7	29.1	30.1	30.7	31.8	32.5
20.0			15.0	23.6	24.0	24.9	25.5	26.6	27.3
22.0				13.6	20.1	21.0	21.5	22.6	23.2
24.0				10.7	16.9	17.8	18.3	19.4	20.0
26.0					14.3	15.2	15.7	16.7	17.3
28.0					11.1	13.0	13.5	14.5	15.1
30.0						7.7	11.7	12.6	13.2
32.0						5.9	10.1	11.0	11.6
34.0						4.2	8.8	9.6	10.2
36.0							4.5	8.4	9.0
38.0								7.4	7.9
40.0									7.0
42.0									6.2
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

B4性能 C/W 60t O/R 6.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	102.0	95.0	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	82.9	81.5	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	68.9	67.6	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	58.6	57.3	43.5	49.7	48.5	53.6	57.6	60.8	61.5
12.0		37.1	40.5	46.7	45.1	50.0	51.4	52.7	53.4
14.0		29.5	36.0	37.6	38.1	39.1	39.7	41.0	41.7
16.0		23.5	29.0	29.8	30.2	31.2	31.8	32.9	33.6
18.0			18.8	24.0	24.4	25.4	26.0	27.1	27.7
20.0			15.0	19.7	20.1	21.0	21.5	22.6	23.2
22.0				13.6	16.6	17.5	18.1	19.1	19.7
24.0				10.7	13.9	14.7	15.3	16.3	16.9
26.0					11.6	12.4	13.0	13.9	14.5
28.0					9.8	10.5	11.0	12.0	12.6
30.0						7.7	9.4	10.3	10.9
32.0						5.9	8.1	8.9	9.5
34.0						4.2	6.9	7.7	8.3
36.0							4.5	6.7	7.2
38.0								5.6	6.3
40.0									5.3
42.0									4.4
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位: ton)

C1性能 C/W 40t O/R 9.2m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	90.6	89.5	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	80.5	79.4	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	71.3	69.9	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	63.2	61.8	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	59.7
14.0		29.5	36.0	41.4	39.4	44.1	46.7	48.1	49.1
16.0		23.5	32.5	36.3	34.7	38.0	38.7	40.1	41.1
18.0			18.8	30.2	30.7	31.8	32.5	33.9	34.9
20.0			15.0	25.0	25.4	26.5	27.2	28.4	29.2
22.0				13.6	21.0	22.0	22.7	23.9	24.6
24.0				10.7	17.5	18.5	19.1	20.3	21.0
26.0					14.7	15.6	16.2	17.4	18.0
28.0					11.1	13.3	13.9	14.9	15.6
30.0						7.7	11.9	12.9	13.6
32.0						5.9	10.2	11.2	11.8
34.0						4.2	8.7	9.7	10.3
36.0							4.5	8.4	9.1
38.0								7.0	7.9
40.0									6.7
42.0									5.6
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位: ton)



13.6m — 50.0m

ブームロックピン無し

C2性能 C/W 40t O/R 8.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	90.6	89.5	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	80.5	79.4	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	71.3	69.9	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	63.2	61.8	43.5	49.7	48.5	53.6	57.6	61.0	63.8
12.0		37.1	40.5	46.7	45.1	50.0	53.9	57.5	59.7
14.0		29.5	36.0	41.4	39.4	44.1	45.9	47.3	48.1
16.0		23.5	32.5	33.7	34.2	35.3	36.0	37.4	38.2
18.0			18.8	26.9	27.3	28.4	29.1	30.4	31.1
20.0			15.0	21.7	22.2	23.2	23.9	25.1	25.8
22.0				13.6	18.2	19.2	19.9	21.0	21.7
24.0				10.7	15.1	16.0	16.7	17.8	18.5
26.0					12.6	13.5	14.1	15.2	15.8
28.0					10.5	11.3	11.9	13.0	13.6
30.0						7.7	10.1	11.1	11.8
32.0						5.9	8.4	9.6	10.2
34.0						4.2	6.8	8.1	8.8
36.0							4.5	6.7	7.5
38.0								5.4	6.3
40.0									5.2
42.0									4.2
危険角度 (°)	-	-	-	-	-	-	20	28	28
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

C3性能 C/W 40t O/R 7.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	90.6	89.5	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	79.8	78.3	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	65.3	63.8	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	54.7	53.3	43.5	49.7	48.5	53.6	55.6	57.0	57.8
12.0		37.1	40.5	45.1	45.1	46.8	47.5	48.9	49.7
14.0		29.5	33.0	33.9	34.3	35.4	36.1	37.4	38.1
16.0		23.5	25.5	26.3	26.7	27.7	28.4	29.6	30.3
18.0			18.8	20.8	21.2	22.2	22.8	24.0	24.7
20.0			15.0	16.7	17.1	18.1	18.7	19.8	20.4
22.0				13.6	13.9	14.8	15.4	16.5	17.1
24.0				10.7	11.4	12.2	12.8	13.8	14.5
26.0					9.3	10.1	10.7	11.7	12.3
28.0					7.6	8.4	8.9	9.9	10.5
30.0						6.9	7.4	8.4	8.9
32.0						5.3	6.0	7.1	7.6
34.0								5.9	6.5
36.0								4.6	5.5
38.0									4.3
危険角度 (°)	-	-	-	-	-	15	33	33	37
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

C4性能 C/W 40t O/R 6.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	102.0	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	80.6	79.1	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	64.6	63.3	50.2	57.4	56.9	62.4	65.6	67.1	66.3
10.0	53.4	52.1	46.5	51.9	52.4	53.6	54.3	55.7	56.5
11.0	45.1	43.7	42.7	43.6	44.0	45.2	45.9	47.2	48.0
12.0		37.1	36.3	37.1	37.6	38.7	39.4	40.7	41.4
14.0		28.1	27.0	27.9	28.3	29.3	30.0	31.2	31.9
16.0		21.8	20.7	21.5	21.9	22.9	23.5	24.7	25.3
18.0			16.2	16.9	17.3	18.2	18.8	19.9	20.6
20.0			12.7	13.4	13.8	14.7	15.2	16.3	16.9
22.0				10.6	11.0	11.9	12.4	13.5	14.1
24.0				8.5	8.8	9.6	10.2	11.2	11.8
26.0					6.9	7.8	8.3	9.3	9.9
28.0					5.0	6.1	6.8	7.7	8.3
30.0						4.4	5.2	6.4	7.0
32.0								5.0	5.8
34.0									4.6
危険角度 (°)	-	-	-	-	15	27	39	42	44
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位: ton)

C5性能 C/W 40t O/R 5.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	76.5	75.2	60.4	67.4	68.7	72.1	72.1		
8.0	59.9	58.7	54.8	58.5	59.0	60.2	60.9	60.9	60.9
9.0	48.6	47.4	46.4	47.3	47.7	48.8	49.5	50.8	51.5
10.0	40.5	39.3	38.3	39.1	39.6	40.6	41.2	42.5	43.2
11.0	34.3	33.1	32.1	32.9	33.4	34.4	35.0	36.2	36.8
12.0		28.3	27.3	28.1	28.5	29.5	30.1	31.2	31.9
14.0		21.2	20.2	21.0	21.4	22.3	22.9	23.9	24.6
16.0		16.2	15.3	16.0	16.4	17.3	17.8	18.9	19.5
18.0			11.7	12.4	12.7	13.6	14.1	15.1	15.7
20.0			9.0	9.6	9.9	10.7	11.3	12.2	12.8
22.0				7.4	7.7	8.5	9.0	10.0	10.5
24.0					5.9	6.7	7.2	8.1	8.7
26.0						5.2	5.7	6.6	7.2
28.0								5.3	5.9
30.0									4.8
危険角度 (°)	-	-	-	25	35	39	48	49	51
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位: ton)



13.6m — 50.0m

ブームロックピン無し

D1性能 C/W 25t O/R 9.2m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	97.8	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	84.6	83.3	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	73.2	71.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	64.1	62.8	46.5	53.2	52.4	57.7	61.8	64.8	66.6
11.0	56.7	55.3	43.5	49.7	48.5	53.6	57.6	59.0	60.0
12.0		37.1	40.5	46.7	45.1	50.0	51.3	52.8	53.8
14.0		29.5	36.0	39.0	39.4	40.8	41.6	43.0	44.0
16.0		23.5	28.9	29.8	30.3	31.5	32.2	33.6	34.4
18.0			18.8	23.3	23.8	24.9	25.6	26.9	27.7
20.0			15.0	18.5	19.0	20.0	20.7	22.0	22.7
22.0				13.6	15.3	16.3	17.0	18.2	18.9
24.0				10.7	12.4	13.4	14.0	15.1	15.8
26.0					10.0	11.0	11.6	12.7	13.4
28.0					7.7	8.9	9.6	10.7	11.4
30.0						6.9	7.7	9.0	9.7
32.0						5.2	6.0	7.3	8.2
34.0								5.8	6.7
36.0								4.5	5.4
38.0									4.3
危険角度 (°)	-	-	-	-	-	15	33	33	37
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

D2性能 C/W 25t O/R 8.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	97.8	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	84.6	83.3	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	73.2	71.9	50.2	57.4	56.9	62.4	66.0	67.7	68.5
10.0	64.1	62.8	46.5	53.2	52.4	57.7	61.8	64.8	65.9
11.0	56.5	54.9	43.5	49.7	48.5	53.6	57.5	58.2	57.4
12.0		37.1	40.5	45.8	45.1	47.7	48.5	50.1	50.5
14.0		29.5	32.7	33.7	34.2	35.4	36.1	37.6	38.4
16.0		23.5	24.7	25.6	26.1	27.3	28.0	29.3	30.1
18.0			18.8	19.9	20.4	21.5	22.2	23.4	24.2
20.0			15.0	15.7	16.2	17.2	17.8	19.1	19.8
22.0				12.5	12.9	13.9	14.5	15.7	16.4
24.0				9.7	10.3	11.2	11.8	13.0	13.7
26.0					7.7	9.0	9.7	10.8	11.5
28.0					5.7	6.8	7.6	9.0	9.6
30.0						5.0	5.8	7.2	8.1
32.0								5.6	6.5
34.0									5.1
危険角度 (°)	-	-	-	-	15	27	39	42	44
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

D3性能 C/W 25t O/R 7.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	97.8	95.0	60.4	67.4	68.7	72.1	72.1		
8.0	81.6	79.9	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	63.9	62.4	50.2	57.4	56.9	62.4	65.0	65.0	63.7
10.0	51.9	50.5	46.5	50.3	50.8	52.1	52.9	54.4	54.9
11.0	43.2	41.8	40.6	41.6	42.1	43.3	44.1	45.5	46.3
12.0		35.2	34.1	35.0	35.5	36.7	37.4	38.8	39.5
14.0		25.9	24.9	25.7	26.2	27.2	27.9	29.2	29.9
16.0		19.7	18.6	19.4	19.9	20.9	21.5	22.7	23.4
18.0			14.2	14.9	15.4	16.3	16.9	18.1	18.8
20.0			10.9	11.6	12.0	12.9	13.5	14.6	15.3
22.0				9.0	9.3	10.2	10.8	11.9	12.5
24.0				6.7	7.2	8.1	8.6	9.7	10.3
26.0					5.0	6.2	6.9	7.9	8.5
28.0						4.3	5.1	6.4	7.0
30.0								4.9	5.7
32.0									4.3
危険角度 (°)	-	-	-	-	25	34	44	46	48
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

D4性能 C/W 25t O/R 6.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	84.1	82.5	60.4	67.4	68.7	72.1	72.1		
8.0	64.1	62.6	54.8	62.1	62.3	64.4	63.2	62.5	61.1
9.0	51.0	49.6	48.4	49.4	49.9	51.2	52.0	53.0	52.1
10.0	41.7	40.4	39.3	40.2	40.7	41.9	42.6	44.1	44.9
11.0	34.9	33.6	32.5	33.4	33.9	35.0	35.7	37.1	37.8
12.0		28.3	27.3	28.1	28.6	29.7	30.4	31.6	32.4
14.0		20.7	19.7	20.5	21.0	22.0	22.6	23.8	24.5
16.0		15.6	14.5	15.3	15.7	16.7	17.3	18.5	19.1
18.0			10.8	11.5	11.9	12.9	13.5	14.6	15.2
20.0			8.0	8.7	9.0	9.9	10.5	11.6	12.2
22.0				6.1	6.6	7.7	8.2	9.3	9.9
24.0						5.5	6.3	7.4	8.0
26.0								5.7	6.4
28.0									4.9
危険角度 (°)	-	-	-	25	41	44	51	52	54
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

D5性能 C/W 25t O/R 5.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	82.0	80.5	67.2	73.2	75.9	75.9			
7.0	60.3	59.0	57.8	58.8	59.3	60.0	60.0		
8.0	46.8	45.5	44.4	45.4	45.8	47.0	47.7	47.7	47.7
9.0	37.6	36.4	35.3	36.2	36.7	37.8	38.4	39.7	40.5
10.0	30.9	29.7	28.8	29.6	30.0	31.1	31.7	32.9	33.6
11.0	25.9	24.7	23.8	24.5	25.0	26.0	26.6	27.8	28.4
12.0		20.8	19.8	20.6	21.0	22.0	22.6	23.7	24.4
14.0		15.0	14.1	14.8	15.2	16.1	16.7	17.8	18.4
16.0		11.0	10.1	10.8	11.2	12.0	12.6	13.6	14.2
18.0			7.2	7.8	8.2	9.0	9.6	10.6	11.2
20.0			4.5		5.9	6.7	7.2	8.2	8.8
22.0						4.7	5.4	6.4	6.9
24.0								4.9	5.4
26.0									4.0
危険角度 (°)	-	-	-	43	47	49	54	56	57
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

E1性能 C/W 10t O/R 9.2m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	88.9	87.6	60.4	67.4	68.7	72.1	72.1		
8.0	75.5	74.2	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	65.1	63.8	50.2	57.4	56.9	62.4	66.0	67.6	68.2
10.0	56.8	55.5	46.5	53.2	52.4	57.1	57.8	58.9	57.9
11.0	49.9	48.2	43.5	47.9	48.5	50.1	50.2	50.4	49.8
12.0		37.1	38.5	39.6	40.2	41.6	42.4	43.7	43.4
14.0		28.5	27.2	28.2	28.8	30.0	30.8	32.3	33.2
16.0		21.2	19.9	20.9	21.4	22.5	23.3	24.7	25.5
18.0			14.9	15.7	16.2	17.3	18.0	19.3	20.1
20.0			11.2	11.9	12.4	13.4	14.1	15.4	16.1
22.0				8.7	9.3	10.5	11.1	12.3	13.0
24.0				5.9	6.5	7.8	8.7	9.9	10.6
26.0						5.5	6.3	7.8	8.6
28.0								5.9	6.8
30.0									5.1
危険角度 (°)	-	-	-	-	35	39	48	49	51
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

E2性能 C/W 10t O/R 8.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	88.9	87.6	60.4	67.4	68.7	72.1	72.1		
8.0	75.5	74.2	54.8	62.1	62.3	67.3	69.6	69.6	69.6
9.0	65.0	63.2	50.2	57.4	56.9	61.6	59.9	59.5	58.3
10.0	51.6	49.9	46.5	49.7	50.3	51.3	50.2	50.3	49.6
11.0	42.2	40.5	39.2	40.3	40.9	42.3	42.7	43.1	42.8
12.0		33.6	32.3	33.4	33.9	35.3	36.1	37.4	37.2
14.0		24.0	22.8	23.7	24.3	25.5	26.2	27.7	28.5
16.0		17.7	16.5	17.4	17.9	19.0	19.7	21.1	21.8
18.0			12.1	12.9	13.4	14.4	15.1	16.4	17.1
20.0			8.3	9.3	9.9	11.0	11.7	12.9	13.6
22.0				6.2	6.8	8.1	9.0	10.2	10.9
24.0						5.6	6.4	8.0	8.7
26.0								5.8	6.8
28.0									5.0
危険角度 (°)	-	-	-	25	41	44	51	52	54
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

E3性能 C/W 10t O/R 7.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	102.0	95.0	67.2	73.2	75.9	75.9			
7.0	83.9	82.1	60.4	67.4	68.7	72.1	71.9		
8.0	61.6	60.0	54.8	59.7	60.4	59.9	58.1	57.6	56.2
9.0	47.7	46.2	44.9	46.0	46.6	48.0	48.0	48.1	47.3
10.0	38.3	36.8	35.6	36.6	37.2	38.5	39.2	40.7	40.3
11.0	31.4	30.0	28.9	29.8	30.4	31.6	32.3	33.8	34.6
12.0		24.9	23.8	24.7	25.2	26.3	27.0	28.4	29.2
14.0		17.6	16.5	17.4	17.8	18.9	19.6	20.9	21.6
16.0		12.7	11.7	12.5	12.9	13.9	14.6	15.8	16.5
18.0			8.2	8.9	9.4	10.3	10.9	12.1	12.8
20.0			4.9	5.9	6.5	7.6	8.2	9.3	10.0
22.0						5.1	6.0	7.2	7.8
24.0								5.3	6.1
26.0									4.3
危険角度 (°)	-	-	-	34	47	49	54	56	57
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

E4性能 C/W 10t O/R 6.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	89.6	87.8	67.2	73.2	75.9	74.2			
7.0	62.9	61.3	59.8	61.0	59.6	58.1	56.1		
8.0	47.3	45.8	44.5	45.6	46.2	46.8	45.5	45.5	44.6
9.0	37.0	35.7	34.5	35.5	36.0	37.3	37.7	38.0	37.6
10.0	29.9	28.5	27.4	28.3	28.8	30.0	30.8	32.2	32.0
11.0	24.5	23.2	22.1	23.0	23.5	24.7	25.3	26.7	27.5
12.0		19.1	18.1	18.9	19.4	20.5	21.2	22.5	23.2
14.0		13.2	12.2	13.0	13.5	14.5	15.1	16.4	17.1
16.0		9.2	8.2	9.0	9.4	10.4	11.0	12.2	12.8
18.0			4.6	5.6	6.2	7.4	8.0	9.1	9.8
20.0						4.6	5.5	6.8	7.4
22.0								4.6	5.5
危険角度 (°)	-	-	25	43	52	53	60	60	61
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

E5性能 C/W 10t O/R 5.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	91.7	90.0	75.6	78.9	77.0				
6.0	60.5	59.0	57.6	58.8	57.7	55.9			
7.0	43.8	42.4	41.2	42.2	42.8	44.0	42.7		
8.0	33.4	32.1	31.0	32.0	32.4	33.6	34.3	34.3	34.3
9.0	26.3	25.1	24.1	24.9	25.4	26.5	27.1	28.5	29.0
10.0	21.2	20.0	19.0	19.8	20.3	21.3	22.0	23.2	23.9
11.0	17.3	16.1	15.2	16.0	16.4	17.4	18.0	19.2	19.9
12.0		13.1	12.2	13.0	13.4	14.3	14.9	16.1	16.7
14.0		8.7	7.8	8.5	8.9	9.8	10.4	11.5	12.1
16.0		5.6	4.2		5.8	6.7	7.2	8.3	8.9
18.0								5.9	6.5
危険角度 (°)	-	-	35	55	56	61	65	65	67
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

F1性能 C/W 0t O/R 9.2m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	99.2	95.0	67.2	73.2	75.9	75.9			
7.0	82.4	81.2	60.4	67.4	68.7	72.1	72.1		
8.0	69.9	68.6	54.8	62.1	62.3	67.3	69.6	68.7	66.7
9.0	60.1	58.8	50.2	57.4	56.9	58.2	56.5	56.2	55.0
10.0	49.4	47.6	46.0	47.3	48.0	47.8	46.8	47.0	46.3
11.0	39.7	38.0	36.6	37.7	38.4	39.9	39.3	39.9	39.5
12.0		31.0	29.7	30.8	31.4	32.8	33.4	34.2	34.1
14.0		21.5	20.3	21.3	21.8	23.1	23.9	25.4	26.0
16.0		15.4	14.2	15.1	15.6	16.8	17.5	18.9	19.7
18.0			9.7	10.8	11.3	12.4	13.1	14.4	15.2
20.0			6.0	7.0	7.7	9.1	9.9	11.1	11.9
22.0					4.7	6.1	7.0	8.6	9.3
24.0								6.1	7.1
26.0									5.1
危険角度 (°)	-	-	-	34	41	49	54	56	57
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

F2性能 C/W 0t O/R 8.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	99.2	95.0	67.2	73.2	75.9	75.9			
7.0	82.4	81.2	60.4	67.4	68.7	72.1	72.1		
8.0	69.0	67.0	54.8	62.1	61.3	59.9	57.9	57.3	55.9
9.0	52.0	50.2	48.6	49.9	48.9	48.3	47.1	47.2	46.3
10.0	40.8	39.1	37.7	38.9	39.5	39.8	39.0	39.5	39.1
11.0	33.0	31.4	30.0	31.1	31.7	33.1	32.8	33.5	33.4
12.0		25.6	24.3	25.4	25.9	27.3	27.8	28.7	28.7
14.0		17.6	16.4	17.4	17.9	19.1	19.8	21.3	21.8
16.0		12.4	11.2	12.1	12.6	13.7	14.4	15.8	16.6
18.0			6.8	7.9	8.5	9.9	10.6	11.9	12.6
20.0					5.1	6.5	7.4	8.9	9.7
22.0								6.3	7.3
24.0									5.1
危険角度 (°)	-	-	25	43	47	53	58	59	59
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

F3性能 C/W 0t O/R 7.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	99.2	95.0	67.2	73.2	75.9	75.9			
7.0	67.3	65.4	60.4	63.9	60.5	58.8	56.6		
8.0	48.8	47.2	45.7	47.0	47.2	46.5	45.1	45.1	44.2
9.0	37.4	35.8	34.5	35.6	36.2	37.6	36.8	37.2	36.7
10.0	29.6	28.1	26.9	27.9	28.5	29.7	30.4	31.1	31.0
11.0	23.9	22.5	21.3	22.3	22.8	24.0	24.8	26.2	26.3
12.0		18.2	17.1	18.0	18.5	19.7	20.4	21.8	22.6
14.0		12.2	11.2	12.0	12.5	13.6	14.2	15.5	16.2
16.0		8.3	7.0	8.0	8.4	9.4	10.1	11.3	12.0
18.0					5.0	6.4	7.1	8.2	8.9
20.0									6.6
危険角度 (°)	-	-	35	49	52	57	63	65	65
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)

F4性能 C/W 0t O/R 6.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	102.0	95.0	80.7	80.7					
5.0	102.0	95.0	75.6	78.9	78.9				
6.0	71.2	69.3	66.9	63.3	59.6	57.5			
7.0	49.3	47.7	46.2	47.4	45.2	44.3	42.9		
8.0	36.5	35.0	33.7	34.8	35.3	35.1	34.2	34.2	34.1
9.0	28.1	26.8	25.9	26.6	27.1	28.2	27.8	28.4	28.3
10.0	22.3	20.9	19.8	20.7	21.2	22.4	22.8	23.7	23.7
11.0	17.9	16.6	15.5	16.4	16.9	18.0	18.7	19.8	20.0
12.0		13.2	12.2	13.1	13.5	14.6	15.3	16.6	17.0
14.0		8.5	7.3	8.3	8.7	9.7	10.4	11.6	12.2
16.0								8.1	8.8
危険角度 (°)	-	20	45	55	60	65	67	67	69
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)



13.6m — 50.0m

ブームロックピン無し

F5性能 C/W 0t O/R 5.4m ブーム

作業半径 (m)	13.6mブーム	18.15mブーム	22.7mブーム	27.25mブーム	31.8mブーム	36.35mブーム	40.9mブーム	45.45mブーム	50.0mブーム
2.5	102.0								
3.0	102.0	95.0							
3.5	102.0	95.0							
4.0	102.0	95.0	83.0						
4.5	95.2	93.1	80.7	75.5					
5.0	72.0	70.2	66.9	62.7	58.5				
6.0	46.7	45.3	43.9	45.0	42.9	41.8			
7.0	33.2	31.9	30.7	31.7	32.2	32.2	31.3		
8.0	24.8	23.6	22.5	23.4	23.9	25.0	24.8	24.8	24.8
9.0	19.1	17.9	16.9	17.7	18.2	19.3	19.9	20.7	20.8
10.0	15.0	13.8	12.8	13.6	14.1	15.1	15.7	17.0	17.2
11.0	11.9	10.7	9.7	10.5	10.9	11.9	12.6	13.8	14.3
12.0		8.2	7.3	8.1	8.5	9.5	10.1	11.2	11.8
14.0								7.5	8.0
危険角度 (°)	-	37	53	61	66	68	72	72	73
伸長状態 (伸長割合%)									
ブーム2 (%)	0	-	-	-	-	-	-	-	100
ブーム3 (%)	0	-	-	-	-	-	-	-	100
ブーム4 (%)	0	-	-	-	-	-	-	-	100
ブーム5 (%)	0	-	-	-	-	-	-	-	100
フック種類	200t	200t	83t	83t	83t	83t	83t	83t	83t
フック質量 (t)	2.60	2.60	1.35	1.35	1.35	1.35	1.35	1.35	1.35
フック掛数	19	14	7	7	7	7	7	7	6

(単位 : ton)