

SR-300R PREMIUM Roughter **EJIB**



<http://www.kato-works.co.jp>

- Before you use the crane, study the instruction manual thoroughly and follow the instructions it contains.
- Some differences may arise between the machine delivered and the photographs in the catalog due to the country the crane will be used in or any added improvements.
Note : The specification may be changed without notice.
- The actual colors of the body and interior may appear slightly different from those shown in this catalogue due to the limitations of photography and printing.

● Contact for enquiry:

KATO KATO WORKS CO.,LTD.
QUALITY & EXPERIENCE
SINCE 1895

SR-300R

9-37, Higashi-ohi 1-chome, Shinagawa-ku, Tokyo, 140-0011, Japan / Tel.: Head Office: Tokyo +81 (0)3 3458-1111 Overseas Marketing Department: Tokyo +81 (0)3 3458-1115 / FAX: Tokyo +81 (0)3 3458-1163

SR-300R

Rough Terrain Crane

PREMIUM
Roughter

EJIB



KATO



Smooth Lifting



30.5m

Number of times necessary for the operator to leave the cabin during jib mounting has been greatly reduced to only 2 with the Ejib!

This has shortened the time required for jib mounting and remarkably making the jib mounting for the operator more easier.



- Tension rod connection
- Release the jib
- Setting the auxiliary hook to the jib tip
- Derrick the boom and swing out the jib



Jib mounting made possible even when boom is retracted

It is a possible for the jib to switch positions to being under the boom while the boom is retracted. It has a jib aerial swingout mechanism thanks to the derrick cylinder. Highly efficient and requires less space for deployment.



■ Tail slewing radius **3.1m**

9.35m

83°

● Boom lifting capacity **SUPERBOOM**

- Boom type..... 4-section round shaped Full Power Boom
- Maximum lifting capacity..... **30t×3.0m**
- Boom length..... **9.35m-30.5m**
- Maximum lifting height..... **31.2m**

● Jib lifting capacity **Ejib**

- Jib type..... 2-section hydraulic luffing power Jib
- Jib offset angle..... **5°-60°**
- Jib length..... **8.7m-13.1m**
- Maximum lifting height..... **44.8m**

Standard & Optional Equipment



▼ Cabin

K•COR



● The K•COR is data logger system which records working status of crane. Record is extractable by the SD card and capable to confirm through K•COR program.



Touch screen control ACS moment limiter

A range of limiting functions to increase Safety during Operation.



▲ Rear step with safety handles



▲ LED combination rear light



▲ Way side lamp (option)



▲ New non slip aluminum step



H-type Outrigger



- Completely retracted **2.31m**
- 3.80m**
- Intermediately extended **5.00m**
- 6.00m**
- Fully extended **6.60m**



▲ Anemometer (option)



▲ Left side view camera (option)



▲ Right side view camera (option)

All new bumper design

● LED head light with Hi and Lo selector

